Form 9–331
Dec. 1973

Form Approved.
Budget Bureau No. 42–R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)

1. oil well ☐ gas well ☐ other

2. NAME OF OPERATOR
Continental Oil Company

3. ADDRESS OF OPERATOR
Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1295' FSL + 2615' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

5. LEASE
LC-058698 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
MCA

8. FARM OR LEASE NAME
MCA Unit

9. WELL NO.
339

10. FIELD OR WILDCAT NAME
Malj. G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 23, T-17S, R-32E

12. COUNTY OR PARISH
Lea

13. STATE
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4004' GR

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐		☐
FRACTURE TREAT	☐		☐
SHOOT OR ACIDIZE	☐		☐
REPAIR WELL	☐		☐
PULL OR ALTER CASING	☐		☐
MULTIPLE COMPLETE	☐		☐
CHANGE ZONES	☐		☐
ABANDON*	☐		X
(other)			

(NOTE: Report results of multiple completion or zone change on Form 9–330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged The well AS Follows: Rigged up 10-25-77 unable to Pull Tbg and Pkr. Cut Tbg AT 2372' and Pulled. Set CMT Retainer AT 2104' and Pumped 250 SX class "C" CMT. Set Pkr AT 899'. Perf w/2 JSPF over A 2' Interval AT 1050' with Through Tbg Gun. Pumped 140 Bbls Fresh Wtr Down Tbg and Did Not Establish Circulation. Pumped Down Csg Annulus w/200 SX Thix set CMT and 350 SX class "C" CMT with 2% CACL2, Displaced CMT. Pulled Tbg + Pkr and spotted 10 SX CMT Surface Plug. Erected Dry Hole Marker and Restored The Surface, 10-28-77.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE _____ DATE 12-7-77

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

USGS-5 MCA Unit Partners (4) File