Submit 3 Copies

## State of New Mexico Energy, ...nerals and Natural Resources Department

Form C-103 Revised 1-1-89

to Appropriate District Office

DISTRICT P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD

P.O. Box 2088 Santa Fe, New Mexico 87504-2088

WELL API NO.		
30-025-353	331	
5. Indicate Type of Lease		

P.O. Diawel DD, Altesia, INVI 60210	STATE X FEE	
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87419	6. State Oil & Gas Lease No. E-7984	
SUNDRY NOTICES AND REPORTS ON WELLS  ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name	
1. Type of Well: OIL OAS WELL WELL X OTHER	Pardner AXO State Com	
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No.	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Pool name or Wildcat Wildcat Mississippian	
4. Well Location [7] Unit Letter $\frac{F}{}$ : 1980 Feet From The North Line and 1980	SO Feet From The West Line	
Section 19 Township 15S Range 35E 1 10. Elevation (Show whether DF, RKB, RT, GR, etc.)	NMPM Lea County	
11. Check Appropriate Box to Indicate Nature of Notice, Ro	eport, or Other Data	

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: FERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PLUG AND ABANDONMENT **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER Spud, conductor, resume drilling, OTHER: surface casing and cement

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Spudded a 20" hole with rat hole machine at 10:30 AM 4-27-2001. Drilled to 40'. Set 40'

of 16" conductor pipe. Cemented to surface. NOTE: Notified Sylvia w/OCD-Hobbs of intent to spud. Resumed drilling a 14-3/4" hole with rotary tools at 1:00 PM 4-30-2001.

TD 420'. Reached TD at 9:30 PM 4-30-2001. Ran 10 joints of 11-3/4" 42# (424.06') of casing set at 420'. 1-Texas Pattern notched guide shoe set at 420'. Insert float set at 382'. Cemented with 310 sacks of Class C with 2% CaCl2 (yield 1.32, weight 14.8). PD 2;30 AM 5-1-2001. Bumped plug to 150 psi, OK. Circulated 10 sacks. WOC. Cut off and welded on rotating head flange. Drilled out at 4:00 AM 5-2-2001. WOC 25 hours and 30 minutes. Reduced hole to 11". Resumed drilling.

I hereby certify that the information above is proc and complete to the best of m	v knowledge and belief.	
SKONATURE Rusty Klein	TITLE Operations Technician	August 30, 2001  TELEPHONE NO. 505/748-1471
(This space for State Use)	FRANCE NEW	- 200°
ANNOUND BY	TITLE	DATE

CONDITIONS OF APPROVAL, IF ANY: