

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals & Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P. O. Box 1980, Hobbs, NM 88240

DISTRICT II
P. O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P. O. Box 2088
Santa Fe, NM 7504-2088

WELL API NO.

30-025-01512

5. Indicate Type of Lease

STATE

FEE

6. State Oil & Gas Lease No.

B-2148

7. Lease Name or Unit Agreement Name

Caprock Maljamar Unit

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1 Type of Well:

OIL
WELL

GAS
WELL

OTHER P & A Injection

2. Name of Operator

The Wiser Oil Company

8. Well No.

86

3. Address of Operator

P.O. Box 2568 Hobbs, New Mexico (505) 392-9797

9. Pool name or Wildcat

Maljamar Grayburg San Andres

4. Well Location

Unit letter N : 660 Feet From The South Line and 1980 Feet From The West Line

Section 21 Township 17S Range 33E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4173'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK

PLUG AND ABANDON

REMEDIAL WORK

ALTERING CASING

TEMPORARILY ABANDON

CHANGE PLANS

COMMENCE DRILLING OPNS.

PLUG AND ABANDONMENT

PULL OR ALTER CASING

CASING TEST AND CEMENT JOB

OTHER:

OTHER:

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/16/00 MIRU Mayo Marrs Casing Pulling Inc. NU BOP. Well had water flow.

11/17/00 Well flowing. Could not release pkr. Worked pkr. Released pkr. POH w/2-3/8" tbg. RIH and set CIBP @ 4180'. RIH with tbg. to 4180. Spotted 25 sks. Class "C" cement on top. Tagged @ 3940'.

11/20/00 RIH with tbg. Tagged cement @ 3940'. Loaded hole with 10# mud. POH. Perforated @ 1375'. RIH w/pkr. Squeezed 50 sks. Class "C" cement. WOC. RIH and tagged cement @ 1215'. POH. RIH and perforated @ 357'. Squeezed 157 sks. Class "C" cement to surface. Left casing and annulus full. RDMO. Cut off WH and anchors. Covered pit and cellar. Installed dry hole marker.

*Note: All procedure changes were approved by Gary Wink NMOCD.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mary Jo Turner
TYPE OR PRINT NAME | Mary Jo Turner

TITLE Production Tech II

DATE December 19, 2000

TELEPHONE NO. (505) 392-9797

(This space for State Use)

APPROVED BY John Jay Robinson

TITLE _____

DATE _____

GWV

JP-G