

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

Table with 4 rows and 2 columns for reporting categories: BEGINNING DRILLING OPERATIONS, RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL, RESULT OF TEST OF CASING SHUT-OFF, RESULT OF PLUGGING OF WELL, and REPAIRING WELL, PULLING OR OTHERWISE ALTERING CASING, DEEPENING WELL.

Midland, Texas. Feb. 23, 1943. Place Date

OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Tide Water Associated Oil Co. Boone Hardin "A" Well No. 3 in the NE/4 of Sec. 19, T. 18S, R. 38E, N. M. P. M., Hobbs Field, Lea County.

The dates of this work were as follows: 12-22-1942 thru 2-12-1943.

Notice of intention to do the work was (was not) submitted on Form C-102 on 12-18-1942 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Set Baker cement Retainer at 3900' and then perforated 7" casing with 3 - 1/2" holes at 2710' and pumped in 450 sacks of cement. Casing tested OK with 1200# pressure before and after drilling plug. Plugged bottom of hole with 20 sacks of cement, 5 sacks of lime, 1 sack of Aquagel and 1/4 sack of Jel-Flake with tubing at 4210' (original depth 4222'). Top of plug at 4084'. Swabbed well dry and the fluid was completely shut off. Drilled cement out to 4125' and swabbed (CONTINUED ON BACK OF SHEET)

Witnessed by E.L. Layman Tide Water Associated Oil Co. Foreman

MIDLAND COUNTY, TEXAS.

Subscribed and sworn before me this

23rd day of February, 1943

C.A. Clarke

[Signature] Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name [Signature]

Position District Foreman

Representing Tide Water Associated Oil Co. Company or Operator

My commission expires June 1, 1943

Address Drawer #1231, Midland, Texas.

Remarks:

Orig. & 2cc Con. Comm., Hobbs, NM. 1cc Tulsa Houston Midland Hobbs

[Signature] Name Title

approximately 1/2 bbl of oil per hour with small amount of gas. After acidizing with 500 gallons of acid well flowed 15 bbl of oil and 15 bbl of water per hour thru 5/16" choke. Put in 3/16" choke and well went dead then installed pumping equipment.