

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	<b>XX</b>
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New Mexico

March 5, 1952

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the.....  
**Gulf Oil Corporation** **West Grimes** Well No. **6** in **SE SW**

Company or Operator **32** Lease **18S** **38E** **Bowers** Field.  
of Sec. **32**, T. **18S**, R. **38E**, N. M. P. M., **Bowers** Field.  
**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION  
Originally completed 10-7-30 - TD 4166' - Initial 9492 bbls oil Est. flowing thru 2-3/8 tubing 24 hours. Plugged back 5-14-49 to 3207' - Initial 14 bbls oil flowing thru 2-3/8 tubing 24 hours with outside gas. Well has been temporarily abandoned since May, 1951.

PROPOSED PLUGGING PROCEDURE

1. Set Baker Model "K" cement retainer at 3100' and squeeze 30 sacks cement in interval from 3100' to 3207' to plug perforations from 3148' to 3162' and 3188' to 3204'.
2. Spot 25' plug on top of cement retainer from 3100' to 3075'.
3. Heavy mud from 3075' to approximately 1025'.
4. Cut off 7" & 9-5/8" casing at approximately 1000'.
5. 50' cement plug from 1025' to 975'.
6. Heavy mud from 975' to 195'.
7. 50' cement plug from 195' to 145'.
8. Heavy mud from 145' to 50'.
9. 50' cement plug from 50' to Surface.
10. Install 4" steel pipe marker to be minimum of 4' above ground level.
11. Fill cellar.

Approved....., 19.....  
except at follows:

Gulf Oil Corporation

Company or Operator  
By *Chas Taylor*  
Position **Area Prod. Supt.**  
Send communications regarding well to  
Name **Gulf Oil Corporation**  
Address **Box 2167, Hobbs, New Mexico**

OIL CONSERVATION COMMISSION

By *Ray Quatrone*  
Title