

DUPLICATE

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

RECEIVED

APR 03 1951

OIL CONSERVATION COMMISSION
HEADQUARTERS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

Table with 4 rows and 2 columns of report categories. The first row is 'REPORT ON BEGINNING DRILLING OPERATIONS'. The second row is 'REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL'. The third row is 'REPORT ON RESULT OF TEST OF CASING SHUT-OFF'. The fourth row is 'REPORT ON RESULT OF PLUGGING OF WELL' with an 'X' in the adjacent box. The right column contains 'REPORT ON REPAIRING WELL', 'REPORT ON PULLING OR OTHERWISE ALTERING CASING', and 'REPORT ON DEEPENING WELL'.

4-2-51

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Shell Oil Company

State "B"

Well No. 3

3

Company or Operator

Lease

NW/4

of Sec. 33

T. 18-S

R. 38-E

N. M. P. M.,

Bowers

Field

Lea

County.

3-29, 3-30-51

The dates of this work were as follows:

Notice of intention to do the work was ~~was not~~ submitted on Form C-102 on 3-29-51 19

and approval of the proposed plan was ~~was not~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Mudded hole: Spotted 10 sax cement plug 3135' - 3000'. Shot pipe @ 1513', 1400', 1250' Recovered 1250' of 4-1/2" casing. Spotted 10 sax cement plug from 0 - 47'. (Bowers Sand 3158' - 3166', Top Anhydrite 1612', Top Salt 1778'). Erected Marker. P & A 3-30-51.

Witnessed by G. L. Goodpaster

Shell Oil Company

Production Foreman

Name

Company

Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

2nd day of April, 19 51

Name John D. Savage
Position Division Exploitation Engineer

[Signature of Notary Public]

Notary Public

Representing Shell Oil Company
Company or Operator

My commission expires My Commission Expires Sept. 16, 1954

Address Box 1457, Hobbs, New Mexico

Remarks:

APPROVED

APR 03 1951

[Signature of Oil & Gas Inspector]

Oil & Gas Inspector

Name

Title

