

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instruction on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 065863

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Lusk Deep Unit

8. FARM OR LEASE NAME

Lusk Deep

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

11. BBL, T, R, M, OR BBL, AND SURVEY OR ALCA

19-19S-32E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

El Paso Products Company

3. ADDRESS OF OPERATOR

c/o Hobbs Pipe & Supply Co., Box 2010, Hobbs, N. M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

UK

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Proposed Plugging Procedures:

1. Spot a 10 sx cement plug on top of present bridge plug.
2. Spot a 25 sx cement plug to cover open perforations.
3. Spot a 25 sx cement plug at stun of 4-1/2" casing.
4. Spot a 35 sx cement plug at base of 8-5/8" casing - (4346')
5. Spot a 25 sx cement plug at 2400' - 2500'.
6. Spot a 25 sx cement plug at 700' - 800'.
7. Spot a 10 sx cement plug at top.
8. Hole will be loaded with mud-laden fluids and a 4" regular marker erected.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE

Agent

DATE

9/16/71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

SEP 17 1971

*See Instructions on Reverse Side

J L GORDON

Faint, illegible text, possibly a header or address, located in the center of the page.

RECEIVED

SEP 21 1971

OIL CONSERVATION COMMISSION

HOUSTON, TEXAS