SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO PULL OR ALTER CASING	Supplementary well history Completion information

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Buffalo Federal Unit		October 4,	, 1963
Well No. 6 is loca	ated 660 ft. from $\begin{bmatrix} \mathbf{S} \\ \mathbf{S} \end{bmatrix}$ line an	d 1980 ft. from $\frac{E}{2M}$ line of	sec. 32
Su/4 SE/4 Sec. 33	7-15-5 R-33-E (Twp.) (Range)	NMPM	
(% Sec. and Sec. No.)	(Twp.) (Range)	(Meridian)	
ildcat	Lea	New Mexico	
(Field)	(County or Subdivision)	(State or Territory)	

The elevation of the derrick floor above sea level is 3742 ft. RT

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Orilled 11" hole to 1444' with rotary tools. Set 8-5/8" OD cave string. Orilled out below with 3" cable tools to TD of 4500'. On 9-5-63, 4-1/2" OD 9.5# J-55 casing was run and set at 4500' with 175 sx. cement. Preceded cement with 200 bbls. of mid. (This revised cementing program approved by Mr. A. R. Brown to Mr. V. E. Staley on 9-4467) Tested casing with 3000 PSI for 30 minutes. Test OK. Pulled 8-5/8" cave string. After WCC 18 hours perforated 4434-53 W/2 SPF and acidized with 1000 gallons. S-O-F with 13,600 gal oil & 23,700# Sand. Swabbed in evaluated. On PT 10-2-63, flow 12 BO, O Bw 24 hrs, CPF 500, TPF 50 16/648 ch.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.		
Company Pan American Petroleum Corporation		
Address	Box 68	V. E. STALEY
	Hobbs, New Mexico	Ву
		Title Area Superintendent

A PART CONTROL OF THE SECOND CONTROL OF THE

· .

ent an own mile of actification

•