State   Stat	DISTRIBUTION SANTA FE	ISTRIBUTION						Form C-103 Supersedes Old C-102 and C-103 Effective 1-1-65		
SUNDRY NOTICES AND REPORTS ON WELLS  1.	U.S.G.S.						State X  5. State Oil &	Fee Gas Lease No.		
E. Name of Operator  Penroc Oil Corporation  2. Address of Operator  P. O. Drawer 831, Midland, Texas 79701  4. Location of Wall  Out terres O , 2111	SUNDRY NOTICES AND REPORTS ON WELLS							111111111111111111111111111111111111111		
Penroc Oil Corporation    Penroc Oil Corporation   S. Femror Leaves Rome Connocon Co	I. OIL GAS							7. Unit Agreement Name		
S. Address of Operator  P. O. Drawer 831, Midland, Texas 79701  4. Location of Well  4. Location of Condition of Well  4. Location of Condition of Condit	2. Name of Operator Penroc Oil Corporation 3. Address of Operator							1		
The Continue of Well  UNIT LETTER O , 2111										
THE S LINE, SECTION 33 TOWNSHIP 185 ANNE 38E NAME.    S								•		
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  PLEFORM REMEDIAL WORK  PULL OR ALTERING CASING  THE TRANSPORT OF THE PROPERTY OF THE PULL AND ABANDON  PULL OR ALTERING CASING  CHANGE PLANS  ALTERING CASING  CHANGE PLANS  CHANGE PLANS  ALTERING CASING  CHANGE PLANS  CHANGE PLANS  CHANGE PLANS  ALTERING CASING  CHANGE PLANS  CHANGE PLANS  ALTERING CASING  CHANGE PLANS  CHANGE PLANS  ALTERING CASING  CHANGE PLANS  ALT	UNIT LETTER	,	FEET PROM					gnated		
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK TELEPRARLICY ARABOON  OTHER  OTHER  17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE RULE 1788.  1/20/72: Spudded 12 noon.  Ran 11 joints 13-3/8", 48# casing set at 378' rotary table.  Cemented w/350 sacks Type H, 2% calcium chloride.  Circulated cement to surface, WOC 18 hours. Tested casing to 750#. Held o.k.  1/27/72: Ran 111 joints 9-5/8" casing as follows: 1500' 32.30#; 1500' 36# H-40, 800' 36#. Set at 3800' rotary table. Cemented w/350 sacks Class "A", 2% calcium chloride. WOC 18 hours. Tested casing to 1000# for 30 minutes. Held o.k.	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\									
PERFORM REMEDIAL WORK  TEMPORATILY ARABOON  PULL OR ALTER CASING  THEM THE Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE NULE 1758.  1/20/72: Spudded 12 noon.  Ran 11 joints 13-3/8", 48# casing set at 378' rotary table.  Cemented w/350 sacks Type H, 2% calcium chloride.  Circulated cement to surface, WOC 18 hours. Tested casing to 750#. Held o.k.  1/27/72: Ran 111 joints 9-5/8" casing as follows: 1500' 32, 30#; 1500' 36# H-40,  800' 36#. Set at 3800' rotary table. Cemented w/350 sacks Class "A",  2% calcium chloride. WOC 18 hours. Tested casing to 1000# for 30 minutes. Held o.k.	16.				<del></del>		ther Data	F:	77777	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propositions).  1/20/72: Spudded 12 noon.  Ran 11 joints 13-3/8", 48# casing set at 378' rotary table.  Cemented w/350 sacks Type H, 2% calcium chloride.  Circulated cement to surface, WOC 18 hours. Tested casing to 750#. Held o.k.  1/27/72: Ran 111 joints 9-5/8" casing as follows: 1500' 32.30#; 1500' 36# H-40, 800' 36#. Set at 3800' rotary table. Cemented w/350 sacks Class "A", 2% calcium chloride. WOC 18 hours. Tested casing to 1000# for 30 minutes. Held o.k.	TEMPORARILY ABANDON	K 🗌			COMMENCE DRI	LLING OPNS.			mT	
1/20/72: Spudded 12 noon. Ran 11 joints 13-3/8", 48# casing set at 378' rotary table. Cemented w/350 sacks Type H, 2% calcium chloride. Circulated cement to surface, WOC 18 hours. Tested casing to 750#. Held o.k.  1/27/72: Ran 111 joints 9-5/8" casing as follows: 1500' 32.30#; 1500' 36# H-40, 800' 36#. Set at 3800' rotary table. Cemented w/350 sacks Class "A", 2% calcium chloride. WOC 18 hours. Tested casing to 1000# for 30 minutes. Held o.k.		or Completed O	perations (Clearly stat	e all partinent de	tails and sive n	netic and described in shall				
800' 36#. Set at 3800' rotary table. Cemented w/350 sacks Class "A",  2% calcium chloride. WOC 18 hours. Tested casing to 1000# for  30 minutes. Held o.k.  18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.  signed Signed by  Joe D. Ramey Title  PATE  JAN 31 197	WORK) SEERULE 1	Spudded Ran 11 Cement Circula	l 12 noon. joints 13-3/8 ed w/350 sac ted cement to	'', 48# cas ks Type H	sing set at 1, 2% calci	378' rotary t um chloride.	able.	of sourcing any pro-	oposes.	
Orig. Signed by  JOE D. Ramey  TITLE  Vice Pres. of Exploration  DATE  1/28/72.	1/27/72:	800' 2% c	36#. Set at 3 alcium chlori	3800' rota: ide. WOC	ry table.	Cemented w/	350 sacks	Class "A".	,	
APPROVED BY JOE D. Romey TITLE DATE	18. I hereby certify that	the information	above is true and com				n_ DATE	1/28/72.		
APPROVED BY DATE TITLE DATE		10	Orig. Signed b	Σγ				1AN 31	1972	
		OVAL, IF ANY	Joe D. Rame	TITLE	·		DATE	77111	<del></del> -	