NO. OF COPIES RECEIVED			Form C-103
DISTRIBUTION			Supersedes Old
SANTA FE	NEW MEXICO OIL CON	SERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
FILE			
U.S.G.S.			5a. Indicate Type of Lease
LAND OFFICE			State X Fee
OPERATOR			5. State Oil & Gas Lease No.
			B-2516
SUNDR	Y NOTICES AND REPORTS ON	IWFIIS	
(DG NOT USE THIS FORM FOR PRO USE "APPLICAT	OPOSALS TO DRILL OR TO DEEPEN OR PLUG TON FOR PERMIT -" (FORM C-101) FOR SU	BACK TO A DIFFERENT RESERVOIR. CH PROPOSALS.)	
14			7. Unit Agreement Name
OIL X GAS WELL OTHER-			
2. Name of Operator			8. Farm or Lease Name
Kirby Petroleum Company			State
3. Address of Operator			9. Well No.
P. O. Box 1745 Houston, Texas 77001			2
4. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER 0 660 FEET FROM THE South LINE AND 2130 FEET FROM			LeamexPenn
,,	FEET FROM THE	LINE AND FEE	T FROM LEGIMEX POINT
THE East LINE, SECTION	on 22 Township 17S	RANGE 33E	.имрм. (
	15. Elevation (Show whether	DF, RT, GR, etc.)	12. County
	4145.6 GL		
16.		<del></del>	Lea ////////
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF IN	TENTION TO:	SUBSEQ	UENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	
Well finishedWaiting on completion			
OTHER	<del></del> U	unit.	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1603.			
Set 13-3/8" casing at Class C cement with 2	431'. Used 442' of 48' calcium cloride mixed ment. WOC 18-1/4 hours	# H-40 ST&C casing.	Cemented with 450 sacks of 1/74. Circulated estimated sing to 1000 psi with rig
Set 9-5/8" casing at 4260'. Used 3506' of 36# K-55 ST&C and 773' of 36# K-55 LT&C casing. Cemented with total of 550 sack cement (250 sacks HOWCO litewate and 300 sacks of Class C) on 11/29/74. WOC 22-1/4 hours. Tested 9-5/8" casing to 1600 psi with rig pump for 30 minutes. Held OK.			
with 6 #/sack salt an	d 0.5% HR-4 mixed at 15, sing held OK. Released	ing. Cemented with a	45' 17# K-55 LT&C 2008' 400 sacks class H cement umped plug with 1450 psi eld OK. Nippled up tubing
Moved out drilling ri	g. Waiting on completion	on unit.	
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
Siere Ciki Want	<b>-</b>	nsulting Engineer	In 7 1075
	TITLE	anginooi	DATE Jan. 7, 1975
APPROVED BY	TITLE		E

CONDITIONS OF APPROVAL, IF ANY: