

32. Acid, Shot, Fracture, Cement Squeeze, Etc.

<u>Depth Interval</u>	<u>Amount and Kind of Material Used</u>
12,300' 9,850'	Set CIBP. Cap w/ 35' cmt. Shot 4 squeeze holes. Cmt. squeeze w/ 350 sx Havco Lite & 520 sx 50/50 Poz "H" + 0.4% Halad-9. Ruse out 5 sx & pull 20 joints. PD @ 8:30 p.m. on 5/19/89.
9592' - 9750'	<u>Perf'd</u> 28 holes. <u>Acidized</u> w/ 3000 gal 7 1/2% HCl using 42 B.S. <u>Frac'd</u> w/ 100m gal 40# X-Link gel & 385m# 20/40 sand.
8701' - 8866'	<u>Perf'd</u> 26 holes. <u>Acidized</u> w/ 3m gals. 7 1/2% HCl using 39 B.S. <u>Frac'd</u> w/ 105m gals. 40# X-Link gel & 414m# 20/40 sand.
7570' - 7584'	<u>Perf'd</u> 2 JSPF, 29 holes. <u>Acidized</u> w/2m gals 7 1/2% HCl using 44 RCNBS. <u>Frac'd</u> w/11m gals. 40# X-Link gel & 12m# 20/40 sand.

**RECEIVED**

**AUG 3 1989**

**OCD  
HOBBS OFFICE**