

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	284		Shells & sand, cemented 10-3/4" csg at 820' w/225 sx
284	805		Red rock & shells cement, 6 aquagel
805	1343		Red rock
1343	1590		Red bed & shells
1590	1566		Red rock
1566	1615		Red bed & potash
1615	1751		Anhydrite
1751	2570		Salt & anhydrite
2570	2716		Salt & potash
2716	2800		Anhydrite & gypsum
2800	2848		Anhydrite & salt
2848	3013		Anhydrite & gypsum
3013	3065		Gypsum
3065	3339		Anhydrite & gypsum
3339	4106		Lime & anhydrite, cemented 7" csg at 4324' w/220 sx cement,
4106	4324		Lime 6 sx aquagel
4324	4484		Gray lime
4484	4490		Sandy lime & anhydrite
4490	4660		Lime
4660	4675		Lime & blue shale
4675	4690		Lime w/brown coarse sand, oil show
4690	4734		Lime
4734	4740		Hard brown lime, 2 1/2" tubing at 4739'
			DEVIATION
			745' straight
			1250' 4 deg off
			1400' 2 deg off
			1500' 1 1/2 deg off
			1560' 1 deg off
			1670' 1/2 deg off
			2300' straight
			3232' straight
			3847' straight
			4250' straight
			4324' straight