


(SUBMIT IN TRIPLICATE)

Land Office Santa Fe  
Lease No. NM 010795  
Unit 5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY



Copy sent to R. B.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

\_\_\_\_\_ Jan. 25 \_\_\_\_\_, 19 56

Federal  
Well No. No. 1 is located 2450 ft. from [N] line and 2310 ft. from [E] line of sec. 5  
18 32 107N  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
X Carroll Lee New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3862 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We will set approximately 650' of 10" pipe to be pulled when 8 5/8" is run and cemented.  
We will set approximately 1050' of 8 5/8" 8 rd. thd. 24# pipe with 50 sacks cement.  
We will set approximately 3750' of new 5 1/2" O.D. 8 rd. thd. 14# casing with 100 sacks cement by Halliburton O.S.S. Co., 5 1/2" to be set approximately 30' below the ends of the pay.  
The salt section should be 1025' to 1575'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Roland Viet Woolley  
Address Box 396,  
1000 Hills, New Mexico  
By [Signature]  
Title Regional Superintendent