

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. B2862
7. Unit Agreement Notice
8. Form or Lease Name Santa Fe
9. Well No. 92
10. Field and Pool, or Willing Vacuum Glorieta
12. County Lea

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator Phillips Petroleum Company
3. Address of Operator Room 806, Phillips Building, Odessa, Texas 79761
4. Location of Well UNIT LETTER <u>K</u> <u>2105</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>33</u> TOWNSHIP <u>17-S</u> RANGE <u>35-E</u> N.M.P.M.

11. Elevation (Show whether DF, RT, GR, etc.)
3960' RKB

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒	ALTERING CASING ☐
COMMENCE DRILLING OPER. ☐	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOBS ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 4-22-76: MI Wells unit, pld rods & pump; unable to pull tbq. Loaded csg w/water, pumped oil in tbq at 2000#, swbd dry. Howco treated Glorieta thru csg perfs 6124-44' w/1500 gals 28% NE FE acid followed by 1500 gals 3% NE HCL acid. Flushed w/24 BW. Max press 2000#, min 600#, ISDP vacuum. AIR 4 BPM. Swbd 2 hrs, 26 BLW.
- 4-23-76: Swbd 2 hrs, 22 BO, 26 BLW. Pld & reset tbq at 6024', Baker anchor catcher at 6021' w/2"x1 1/4"x16' pump at 6021'. Released unit.
- 4-24/25-76: P/48 hrs, no gauge.
- 4-26-76: P/24 hrs, 37 BO, 21 BSW.
- 4-27-76: P/24 hrs, 20 BO, 26 BSW.
- 4-28-76: P/24 hrs, 25 BO, 20 BSW, GOR 1120/1, perfs 6124-44': Restored to production.

BOP Eqpt: Series 900, 3000# WP, double, w/one set pipe rams, one set blind rams, manually operated.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Engineering Advisor DATE 4-30-76
Only Signed by Harry S. Sorenson DATE MAY 1 1976
APPROVED BY Harry S. Sorenson TITLE Director DATE MAY 1 1976
CONDITIONS OF APPROVAL, IF ANY: