State of New Mexico inerals and Natural Resources Department Energ

Form C-103 Revised 1-1-89

DISTRICT P.O. Box 1980, Hobbs, NM 88240

P.O. Drawer DD, Artesia, NM 88210

DICTRICT III

OII.	CONSI	TR VA	TION	DIVISION

	P.O. Box 20	88
Cana Ta	NI. Mania	97504 2000

Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-20941	
5. Indicate Type	e of Lease STATE X	FEE _

1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No. B-1722					
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name					
1. Type of Well: OIL OAS WELL X WELL OTHER	New Mexico "N" State					
2. Name of Operator Texaco Exploration and Production Inc.	8. Well No.					
3. Address of Operator P.O. Box 730 Hobbs, New Mexico 88240	9. Pool name or Wildcat Vacuum Glorieta					
4. Well Location Unit Letter M: 560 Feet From The South Line and	560 Feet From The West Line					
Section 30 Township 17-S Range 35-E	NMPM Lea County					
10. Elevation (Show whether DF, RKB, RT, GR, etc., 3998 ' DF						
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data						
NOTICE OF INTENTION TO:	UBSEQUENT REPORT OF:					
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING					
TEMPORARII Y ARANDON CHANGE PLANS COMMENCE DRII	LING OPNS DILIG AND ARANDONMENT X					

- 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 11/25/91 - 12/05/91
 - Notified NMOCD, MIRU w/P&A equip., TOH w/prod equip Starting date 11-25-91.
 - Tied onto 2 7/8" csg w/pump truck. Established rate of 5 BPM 2. with no pressure into Glorieta perfs (6004'-6062')

OTHER:_

CASING TEST AND CEMENT JOB L

- Pmp 300 sxs Class C cmt w/2% CAL CHL into perfs @ 6004'-3. 6062'.
- Followed cmt w/6 bbls of salt gel mud, SION. 4.
- Tagged cmt @ 3112', TIH w/1 5/8" drillpipe w/tailpipe @ 3085', loaded hole w/brine gel, TOH w/drillpipe.
- Perf 2 sqz holes @ 350', established circ to surface thru sqz holes, pmp 120 sxs Class C cmt dn 2 7/8" csg until circ to surface thru 8 5/8" annulus & to surface of 2 7/8" csg.
- Cut wellhead, installed dry hole marker, cleaned location. 7. Completion date 12-05-91.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.						
SIGNATURE MARY	mæ Engineer's Assistant	рате _12-20-91				
TYPE OR PRINT NAME M.C. Duncan		TELEPHONE NO. 393-7191				
(This space for State Use)		JAN 27				
APPROVED BY Light Fr. Timo Bally	ME OIL & GAS [REPECTO	DATE				

CONDITIONS OF APPROVAL, IF ANY:

PULL OR ALTER CASING

OTHER: