

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

API #30-025-27342

5a. Indicate Type of Lease
State For

5. State Oil & Gas Lease No.
B-2245-6

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL GAS WELL OTHER- water injection

7. Unit Agreement Name
East Vacuum GB/SA Unit

Name of Operator
Phillips Petroleum Company

8. Farm or Lease Name East
Vacuum GB/SA Unit Tr 2054

Address of Operator
4001 Penbrook, Rm 401, Odessa, TX 79762

9. Well No.
003

Location of Well
UNIT LETTER M 1000 FEET FROM THE south LINE AND 150 FEET FROM

10. Field and Pool, or Wildcat
Vacuum GB/SA

THE west LINE, SECTION 20 TOWNSHIP 17-S RANGE 35-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3976.1 GR (unprepared)

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK

TEMPORARILY ABANDON

PULL OR ALTER CASING

OTHER

PLUG AND ABANDON

CHANGE PLANS

REMEDIAL WORK

COMMENCE DRILLING OPNS.

CASING TEST AND CEMENT JOBS

OTHER

ALTERING CASING

PLUG AND ABANDONMENT

Total Depth

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-15-81 Cactus Drlg spudded w/12-1/4" bit to 370' @ 11:00 A.M. Ran 8-5/8", 24#, K-55 csg set @ 369'. Cmtd w/400 sxs Class "C" w/2% CaCl₂ & 1/4# Flocele/sx. Circ. 90 sxs to surface. Tested csg 14 hrs after plugdown; Temp. of cmt, 75°, Temp. in formation, 60°; cmt strength @ time of test, exceeds 500 psi; time cmt in place prior to test, 14 hrs. Drl'd ahead w/7-7/8" bit.

5-16/26-81 Reached TD of 4800'. Ran logs.

5/27/81 Ran 4-1/2", 11.6#, N-80 csg set @ 4800'. Cmtd w/800 sxs TLW w/10% Diacele D, 12# salt, 1/4# Flocele & 3# gilsonite followed w/400 sxs Class "C" w/6#/sx salt. Circ 240 sxs. Released rig; prep to complete.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W.J. Mueller TITLE Sr. Engineering Specialist DATE 6-4-81

APPROVED BY Jerry Saxon TITLE Dist. L. Supt. DATE JUN 9 1981

CONDITIONS OF APPROVAL, IF ANY: