

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO
NM-63365
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
EWT "1" Federal
9. WELL NO.
#1
10. FIELD AND POOL, OR WILDCAT
N. Young Bone Spring
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 1, T18S, R32E
12. COUNTY OR PARISH
Lea
13. STATE
NM

1. OIL WELL GAS WELL OTHER
2. NAME OF OPERATOR
Harvey E. Yates Company
3. ADDRESS OF OPERATOR
P.O. Box 1933, Roswell, New Mexico 88202
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below)
At surface 330' FSL & 2310' FEL
14. PERMIT NO
30-025-30146
15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3899.6 GL

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETION
ABANDON*
CHANGE PLANE

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(Other) Spud, surface & inter. csg

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/28/87 Spud well @ 1:00 am
Ran 405 ft, 13 3/8, J-55, 54.5 csq, Set @ 403 ft.
Cemented w/425 sks Class "C" w/2% CaCl, Circ 64 sks to pit
WOC 12 hrs, Test csg to 600 psi for 30 min-Held ok

12/30/87 Ran 2900 ft of 8 5/8, 32 & 24#, J-55 csg, Set @ 2890 ft
Cemented w/1000 sks filler & 200 sks Class "C" w/2% CaCl
Circ 234 sks to pit
WOC 12 hrs
Test csg to 1200 psi for 30 min-Held ok

SJS

18. I hereby certify that the foregoing is true and correct

SIGNED A. M. Young NM Young TITLE Drilling Superintendent DATE 1/5/88

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side