

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico		
Rustler	2196				
T. Anhy		T. Canyon	10980	T. Ojo Alamo	T. Penn. "B"
T. Salt		T. Strawn	11334	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt		T. Atoka	11632	T. Pictured Cliffs	T. Penn. "D"
T. Yates	3650	T. Miss		T. Cliff House	T. Leadville
T. 7 Rivers		T. Devonian		T. Menefee	T. Madison
T. Queen	4646	T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg	4786	T. Montoya		T. Mancos	T. McCracken
T. San Andres	5234	T. Simpson		T. Gallup	T. Ignacio Otzte
T. Glorieta	6856	T. McKee		Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger		T. Dakota	T.
T. Blinebry		T. Gr. Wash		T. Morrison	T.
T. Tubb		T. Delaware Sand		T. Todilto	T.
T. Drinkard		T. Bone Springs 2nd-8689		T. Entrada	T.
T. Abo		T. 3rd B. Springs-9386		T. Wingate	T.
T. Wolfcamp	10032	T. Lwr. Strawn -11423		T. Chinle	T.
T. Penn		T.		T. Permian	T.
T. Cisco (Bough C)		T.		T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	445	445	Surface, Redbeds	7140	7380	240	Dolo, SS
445	2000	1555	Anhy, Redbeds	7380	7740	360	Dolo
2000	2200	200	SS, Sh	7740	8060	320	Dolo, Cht
2200	2300	100	Anhy, Sh	8060	8900	840	Dolo, Cht, LS, Sh
2300	2800	500	Anhy, Sh, SS	8900	9170	270	Dolo, SS
2800	3700	900	Anhy, Sh	9170	9460	290	Dolo, Sh, Cht, SS
3700	3810	110	Anhy, Dolo, Sh	9460	9820	360	SS, Dolo, Slstn
3810	4420	610	Anhy, Sh	9820	10460	640	LS, Cht, SS, Sh
4420	4690	270	Anhy, SS	10460	11480	1020	Dolo, Cht, Sh, LS
4690	5000	310	Anhy, SS, Dolo, Sh	11480	11640	160	LS
5000	5240	240	Anhy, Dolo, SS	11640	11905	265	SS, LS, Sh
5240	6000	760	Dolo				
6000	6220	220	Dolo, LS				
6220	6680	460	Dolo, Cht				
6680	7000	320	LS, SS				
7000	7140	140	SS, Dolo, LS				

1
MAR 30 1990
OCC
HOBBS OFFICE