

UNITED STATES
DEPARTMENT OF THE INTERIOR

AUG - 7 2000
M. Oil & Gas Division
625 N. F. Smith Dr.
Monte, NM 83240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Xeric Oil & Gas Corporation

3. Address and Telephone No.

P.O. Box 352, Midland, TX 79702 (915) 683-3650

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit B, 890 FNL & 1650 FEL
Sec. 29, T19S, R35E, NMPM

6. If Indian, Allottee or Tribe Name

P 3: 03

7. If Unit or CA, Agreement Designation

NMM71083A

8. Well Name and No.

West Pearl Queen Unit #1

9. API Well No.

30-025-03246

10. Field and Pool, or Exploratory Area

Pearl (Queen)

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 7-24-00 (1) Notify BLM, Andrea
(2) Tag TOC @ 4724'.
(3) Mix and circulate w/ MLF.
7-25-00 (4) Spot 25 sx cmt. @ 3090-2712', as per NMOCD.
7-26-00 (5) Sqz. 25 sx cmt. w/ 2% CaCl under pkr @ 1508', thru perms @ 1746' @ 1 Bbl/Min.
@ 600 PSI., Displaced TOC to 1696', SIP @ 500 PSI, Tag TOC @ 1695'.
(6) Spot 60 sx cmt. @ 428'.
7-27-00 (7) Tag TOC @ 235'.
(8) Circ. 10 sx cmt. 30 - Surface.
(9) Install dry hole marker & backfill pit and cellar.

Approved as to plugging of the well bore.
Lifted under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Agent

Date 07/31/00

(This space for Federal or State office use)

(ORIG. SGD.) DAVID F. GLASS

Title

PETROLEUM ENGINEER

Date

AUG 24 2000

Approved by
Conditions of approval, if any: