NEW MEXICO OIL CONSERVATION CO-MISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL			
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING			
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL			
NOTICE OF INTENTION TO DEEPEN WELL	The state of the s			
Monument, New)	Mexico Nay 24, 1936			
AL CONSERVATION COMMISSION,	Pace Date			
anta Fe, New Mexico.				
entiemen:				
ollowing is a notice of intentiton to do certain work as	described below at the			
Amerada Petroleum Corporation Company or Operator Lease	State "T" Well No. 1 in SE1 SW			
Sec. 25 , T. 19 , R. 36	_, N. M. P. M., Monument			
County.				
122 40# 8-5hd. New Lapweld casing the Halliburton Methdo with 150 sack. Cement plug will be drilled out of blowed to stand undisturbed for one hou	casing and the hole bailed to hottom and			
122 40# 8-5hd. New Lapweld casis by the Halliburton Methdo with 150 sack Cement plug will be drilled out of allowed to stand undisturbed for one how to determine if any water has accumulate	ng was set in this well at 208° and comens of coment.			
122 40# 8-5hd. New Lapweld casis by the Halliburton Methdo with 150 sack Cement plug will be drilled out of cliowed to stand undisturbed for one how of determine if any water has accumulate	ng was set in this well at 208° and cements of cement. casing and the hole bailed to bottom and ir. The bailer will be run to bottom agained. If no water has accumulated then drill			
122 40# 8-5hd. New Lapweld casis by the Halliburton Methdo with 150 sack Cement plug will be drilled out of llowed to stand undisturbed for one how of determine if any water has accumulate	ng was set in this well at 208 and comen s of coment. casing and the hole bailed to hottom and			
12½ 40% 8-5hd. New Lapweld casis by the Halliburton Methdo with 150 sack. Coment plug will be drilled out of allowed to stand undisturbed for one how of determine if any water has accumulated the resumed. MAY 26 1936	ng was set in this well at 208° and cements of cement. casing and the hole bailed to hottom and ir. The bailer will be run to bottom agained. If no water has accumulated then drill			
12½ 40# 8-5hd. New Lapweld casis by the Halliburton Methdo with 150 sack. Coment plug will be drilled out of allowed to stand undisturbed for one how to determine if any water has accumulated till be resumed. MAY 26 i936 proved	ng was set in this well at 208° and cements of cement. casing and the hole bailed to bottom and ir. The bailer will be run to bottom agained. If no water has accumulated then drill			
12½ 40% 8-5hd. New Lapweld casis by the Halliburton Methdo with 150 sack. Coment plug will be drilled out of allowed to stand undisturbed for one how of determine if any water has accumulated the resumed. MAY 26 i936	ng was set in this well at 208° and cements of cement. casing and the hole bailed to hottom and ir. The bailer will be run to bottom agained. If no water has accumulated then drill DUPLICATE			
12½ 40% 8-5hd. New Lapweld casis by the Halliburton Methdo with 150 sack. Coment plug will be drilled out of allowed to stand undisturbed for one how of determine if any water has accumulated the resumed. MAY 26 i936	ng was set in this well at 208° and cements of cement. casing and the hole bailed to hottom and ir. The bailer will be run to bottom agained. If no water has accumulated then drill DUPLICATE			
12½ 40# 8-5hd. New Lapweld casis by the Halliburton Methdo with 150 sack. Coment plug will be drilled out of allowed to stand undisturbed for one how to determine if any water has accumulated till be resumed. MAY 26 i936 proved	DUPLICATE Amerada Petrolaim Corporation Company or Operator By Ja Marky			
12½ 40# 8-5hd. New Lapweld casis by the Halliburton Methdo with 150 sack. Cement plug will be drilled out of allowed to stand undisturbed for one house determine if any water has accumulate will be resumed. MAY 26 1936	DUPLICATE Amerada Petrolaim Corporation Company or Operator By Ja Markey Position Farm Boss			
122 40# 8-5hd. New Lapweld casis by the Halliburton Methdo with 150 sack. Coment plug will be drilled out of allowed to stand undisturbed for one how to determine if any water has accumulate will be resumed. MAY 26 1936 pproved MAY 26 1936 peroved sept as follows:	DUPLICATE Amerada Petrolaim Corporation Company or Operator By Jallander Position Farm Boss Send communications regarding well to			

A CANADA CONTRACTOR OF THE SECOND SEC

The state of the state of the state of

	:		
*			

		eramina		
			* 114 T	

.