

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-05640
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	B. V. CULP (NCT-A)
8. Well No.	8
9. Pool name or Wildcat	WSW; SAN ANDRES
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	
2. Name of Operator Chevron U.S.A. Inc.	
3. Address of Operator P.O. Box 1150, Midland, TX 79702	
4. Well Location Unit Letter <u>F</u> : <u>2310</u> Feet From The <u>NORTH</u> Line and <u>2239</u> Feet From The <u>WEST</u> Line Section <u>19</u> Township <u>19S</u> Range <u>37E</u> NMPM LEA County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

CHEVRON PROPOSES TO:

RIH W/2-3/8" PUP CUT @ 45 DEGREES & 2-3/8" TBG TO 4900'. BALANCE A CMT PLUG 4900'-4050'. MUD HOLE F/TOC TO 3138'. **SET CMT RET @ 3088'. SQZ 250 SX CMT BELOW RET OR UNTIL SQZ PRES RISES 300 PSI ABOVE INITIAL SQZ PRES. PLACE 20' CMT ABOVE RET. MUD HOLE F/TOC - 466'. PERF (4) 1/2" HOLES @ 416'. PLACE CMT RET @ 366' & SQZ 60 SX CMT BELOW RET & PLACE 20' CMT ABOVE RET. MUD HOLE TO 50' AND BRING CMT F/50'-SURF.

**EFFORTS TO RE-ENTER & REPAIR 5-1/2" CSG FAILED WHEN A 4-3/4" MILL IS THOUGHT TO HAVE EXITED THE 5-1/2" & 9-5/8" CSG @ 3138', AND DRILLED OUTSIDE CSG TO 3165'. IF UNABLE TO ENTER WELL, PLUGGING WILL BEGIN WITH SETTING CMT RETAINER @ 3088'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J. K. Ripley TITLE TECHNICAL ASSISTANT DATE 7/25/97

TYPE OR PRINT NAME J. K. RIPLEY TELEPHONE NO. (915)687-7148

(This space for State Use) ORIGINAL SIGNED BY CHRIS WILLIAMS
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

JUL 30 1997

JC

2/10/98