## STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

WO. OF COMIES RECEIVED		
DISTRIBUTION		
SANTA PE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR	T	

COMPERANTION DIVISION	
P. O. BOX 2088	Form C-193 Revised 19-1-7
NTA FE, NEW MEXICO 87501	netracu is-t-i

SANTA PE	SANTA FE, NE\	N MEXICO 87501	
FILE			Sa. Indicate Type of Lease
U.S.G.S.	-		State X Foe
LAND OFFICE	-		5. State Oil & Gas Lease No.
OPERATOR	لـ		B1533-122
SUND: PR ROP MET USE THIS FORM FOR PR	RY NOTICES AND REPORTS OF	WELLS	
	TOPOSALS TO ORTLE OR TO GEEPEN OR PLUG TION FOR PERMIT - ** (FORM C-101) FOR SE	CH PROPOSALS.)	
1. OIL 👽 645			7. Unit Agreement Name
weit X weit	OTHER-		
2, Name of Operator			8. Farm or Lease Name
Amerada Hess Corporat	ion		State "O"_
3. Address of Operator			9. Well No.
Drawer D, Monument, New Mexico 88265		4	
Location of Well		10. Field and Pool, or Wildcat	
		Eunice/Monument G/SA	
UNIT LETTER A . 660 PEET FROM THE EAST LINE AND 660 PEET FROM			MON TITITITITITITITITITITITITITITITITITITI
No set le	20 100	200	
THE WOLLI LINE, SECT	10N 30 TOWNSHIP 19S	RANGE 3/E NI	now: {
mmmmm	CTTT CO. CC.	OC DT CD	
	15. Elevation (Show whether		12. County Lea
	3639' D	T'	Teg ////////
	Appropriate Box To Indicate INTENTION TO:	•	Other Data ENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABAHDON		COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	
		OTHER	
OTHER	<u> </u>		
work) SEE RULE 1103.			iding estimated date of starting any proposed
tbg. & checked top of 3839' & pushed bridge 3831'. Set inflatable open hole at 3866' and tested. Set Lynes bridge Ran pkr. & tbg. & set open hole fr. 3843' to San Andres zone in open rock salt as diverter	ovember 8, 1984 - Pulle cement inside 6-5/8" csc plug to 3970'. Ran dummer pkr. in open hole at 30 d swab tested. Set infide plug in open hole at okr. in 6-5/8" csg. at 10 3874' w/500 gal. 15% November 1843' to 3874. Swab tested. Pulled to motor, connected electroscent	o. at 3839!. Drld. cem bailer & plugged back 878' and swab tested. latable pkr. in open ho ad dumped 1 sk. cement 3826' and acidized Gray E FE acid. Swab tested 4' w/1000 gal. 15% HCl tbg. & pkr. Ran tbg.,	ment & bridge plug at a copen hole fr. 3970' to Set inflatable pkr. in ple at 3874' and swab on top of bridge plug. The burg San Andres zone in a Acidized Grayburg acid in two stages using pump and rods. Installed
Status changed from qu	as well in an oil pool to	a numping oil well.	
No test reported.	•		
iff. I hereby certify that the information	n shove is true and complete to the beat	of my knowledge and belief.	
-0	)	-	
a Ba. V.	. 1	Curous Adm Com	_ 17 12 04
HIGHED CY THAT	4 YITLE	Supv. Adm. Ser.	DATE 11-13-84
og in the second	AD COM SAN DESTANA		NOV 1 6 1984