

FEELAND

PI # 30-025-05902

DF: 3567'

GL: 3554'

T/ ANHYDRITE 1035'
T/ SALT 1151'

17-1/2" HOLE
225 SX

13-3/8" 36 PPF
CSG AT 297'
TOC AT 1096'
TOC AT 1440'

T/ YATES 2272'

T/ MONUMENT
LIME 2405'

T/ STUART SD 3087'

T/ SAN ANDRES 3567'

12-1/4" HOLE
2000 SX

8-3/4" HOLE
300 SX

9-5/8" 36 PPF
CSG AT 2388'

TOL AT 3661'

7" 23 PPF CSG
AT 3710'

TOC AT 4480'

ANNULUS IS LOADED
WITH 76.5° API OIL
BLANKET
TBG SET AT 4495'.

6-1/4" HOLE
160 SX

CIBP AT 5000'

4515'-55'
4600'-4715'
4750'-70'
4780'-90'
4830'-4920'
PBT'D AT 4991'

5" 15 PPE LINER AT 5065'

T/ SAN ANGELO 5570'
T/ CLEARFORK 5683'

OH TD AT 5712'

DWN	3-29-89	S.A.H.	APPROVED		E-M-E SWD SYSTEM SWD WELL #5 Rice Engineering Corporation Great Bend, Kansas	SCALE NONE
						DRG. NO.