NF -- EXICO OIL CONSERVATION C SSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of no	tice by checking below.	
SOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
SOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		
	Towns December 91 1086	_
	nk, Texas, December 21, 1936 Place Date	
IL CONSERVATION COMMISSION,		
anta Fe, New Mexico.		
entlemen:	THE STATE OF COMMAND	
ollowing is a notice of intentiton to do certain work as	described below at the THE TEXAS COMPANY	
J. W. Coop		NE
Company or Operator Lease	, N. M. P. M., Monument Fi	
	, N. M. P. M., MONTHISH V	el a
Lea County.		
T. D. 3760' Lime. Set and cemented 3742' of 7" t 3760' with 350 sacks Trinity co	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing	Jt at
T. D. 3760' Lime. Set and cemented 3742' of 7" t 3760' with 350 sacks Trinity co PM 12-20-36. Anticipate drilling plug and	OD 24# 10thd seamless casing (124	at
T. D. 3760' Lime. Set and cemented 3742' of 7" t 3760' with 350 sacks Trinity co PM 12-20-36. Anticipate drilling plug and	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing	at
T. D. 3760' Lime. Set and cemented 3742' of 7" t 3760' with 350 sacks Trinity co PM 12-20-36. Anticipate drilling plug and	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing	at
T. D. 3760' Lime. Set and cemented 3742' of 7" t 3760' with 350 sacks Trinity co PM 12-20-36. Anticipate drilling plug and	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing	at
T. D. 3760' Lime. Set and cemented 3742' of 7" t 3760' with 350 sacks Trinity co PM 12-20-36. Anticipate drilling plug and	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing	at
T. D. 3760' Lime. Set and cemented 3742' of 7" t 3760' with 350 sacks Trinity co PM 12-20-36. Anticipate drilling plug and PM 12-23-36.	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing testing casing by pressure method	at
T. D. 3760' Lime. Set and cemented 3742' of 7" t 3760' with 350 sacks Trinity co PM 12-20-36. Anticipate drilling plug and PM 12-23-36.	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing testing casing by pressure method THE TEXAS COMPANY	at
T. D. 3760' Lime. Set and cemented 3742' of 7" t 3760' with 350 sacks Trinity co PM 12-20-36. Anticipate drilling plug and PM 12-23-36.	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing testing casing by pressure method THE TEXAS COMPANY	at
T. D. 3760' Lime. Set and cemented 3742' of 7" t 3760' with 350 sacks Trinity co PM 12-20-36. Anticipate drilling plug and PM 12-23-36.	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing testing casing by pressure method THE TEXAS COMPANY By Position District Superintendent	at
T. D. 3760' Lime. Set and cemented 3742' of 7" t 3760' with 350 sacks Trinity co PM 12-20-36. Anticipate drilling plug and PM 12-23-36.	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing testing casing by pressure method THE TEXAS COMPANY	at
T. D. 3760' Lime. Set and cemented 3742' of 7" at 3760' with 350 sacks Trinity company in the second sacks Trinity company in the second secon	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing testing casing by pressure method THE TEXAS COMPANY By Position District Superintendent	at
T. D. 3760' Lime. Set and cemented 3742' of 7" It 3760' with 350 sacks Trinity co SPM 12-20-36. Anticipate drilling plug and SPM 12-23-36.	OD 24# 10thd seamless casing (124 mmon cement. Completed cementing testing casing by pressure method THE TEXAS COMPANY By Position District Superintendent Send communications regarding well to	at

1 - 14 - 14 - 15 - 1844 <u>1</u> (1985年7月日日本海道) (1975年)

والمراجع والمراجع والمراجع والمعامل والمراجع والمتابع والمتعامل والمتعامل والمتابع والمتابع والمتابع

on the public parallel from a least to the

Control of the Contro

Mark Garage St. R. Commercial