


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS OF WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten ~~days~~ ^{hours} after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	X
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Monument, New Mexico,
Place

November 27, 1946
Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation L. M. Lambert Well No. 3 in the
Company or Operator Lease
NE 1/4 NE 1/4 of Sec. 6, T. 20, R. 37E, N. M. P. M.,
Monument Field, Lea County.

The dates of this work were as follows: November 20th and 22nd, 1946

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____ 19____
and approval of the proposed plan ~~was~~ (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3888' Total Depth Line, Killed well with 250 barrels of water, pulled tubing, ran Baker Model K Cement Retainer and set at 3705' as bridging plug and dumped 2 sacks of common cement on top. Pumped down Halliburton Test Plug and found hole in Casing at 1738' pumped into casing with 500# and got returns between 6 5/8" and 8 5/8" Casing. Ran Baker Retrievable Retainer and set at 1784', 1751' and 1740' and tested with 1800# and was OK, set at 1720' and got returns between 6 5/8" & 8 5/8" Casing. Ran Baash Ross Model LV Casing knife and cut pipe at 2196' and pulled out 70 jts 6 5/8" Casing.

Witnessed by N. D. Jarred, Amerada Pet. Corp. Farm Boss
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

27 day of November, 19 46

Name Don Tippin

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corp.
Company or Operator

My commission expires Nov 29 1946

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date NOV 29 1946

Res. Yorkrough
Name
Oil & Gas Inspector
Title