

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-05930

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ TA'd GAS WELL ☐ OTHER

2. Name of Operator
Amerada Hess Corporation

3. Address of Operator
Drawer D, Monument, New Mexico 88265

4. Well Location
Unit Letter H : 2084 Feet From The North Line and 660 Feet From The East Line
Section 6 Township 20S Range 37E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

7. Lease Name or Unit Agreement Name

North Monument G/SA Unit
Blk. 20

8. Well No.
8

9. Pool name or Wildcat
Eunice Monument G/SA

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: Repair log & TA'd well. ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-26 thru 7-7-92

MIRU Ram Well Svc., removed well head & installed BOP. Released pkr. & TOH w/tbg. & pkr. TIH w/7" Elder lok-set RBP set at 3476'. TIH w/7" pkr. & pres. RBP to 2000#. Held OK. TOH w/pkr. Dumped 12 sks. sand on top RBP. Schlumberger ran CBL-GR-CCL fr. 3412' - 100'. Located cement top at 2400'. Perf. csg. at 2395' w/4 jet shots. TIH w/7" SV EZ drill cement retainer set at 2298'. Halliburton pumped 325 sks. Class C cement slurry at 1.5 BPM, 1000#. WOC. TIH w/6-1/8" bit, checked cement at 2288' & drld. cement, retainer & cement to 2428'. Press. tested csg. fr. 0' - 3426' to 540# for 30 min. Held OK. Chart attached. Ran bit & circ. sand fr. 3426' - 3476' & TOH. TIH w/retrieving tool, latched onto RBP & TOH. TIH w/pkr. on 2-3/8" tbg. & set pkr. at 3481'. Removed BOP & installed well head. Circ. 150 bbls. fresh water mixed w/pkr. fluid. RDPU, cleaned location & TA'd well. Amerada Hess Corporation respectfully request a continued TA'd status on well for future NMGSAU operations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. L. Wheeler, Jr. TITLE Supv. Adm. Svc. DATE 8-26-92

TYPE OR PRINT NAME R. L. Wheeler, Jr. TELEPHONE NO. 393-2144

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

**This Approval of Temporary
Abandonment Expires** 9-1-97

AUG 31 '92

RECEIVED

AUG 28 1992

JCD HOSBS OFFICE