

8470	105	3	.05241	5.50	
8550	80	2 1/2	.09366	3.44	
8620	70	2	.03492	2.44	
8715	95	3 3/4	.06654	6.32	
8765	50	4 3/4	.08309	4.15	
8815	50	4	.06993	3.50	
8916	101	7	.12278	12.40	221.38
8950	34	8 1/4	.14499		
8980	30 } 72	8 1/4	.14499	11.89	
8998	18	8 1/4	.14499		
9028	30	7 3/4	.13609	1.86	
9070	42	8	.14054		
9100	30 } 72	8	.14054	10.12	245.25'
9130	30 } 75	8	.14054		
9175	45	8	.14054	10.54	
9201	26	7 3/4	.13609	3.54	
9300	99	7	.12278	12.16	
9340	40	6 3/4	.11836	4.73	
9380	40	6 1/4	.10952	4.38	
9460	80	6	.10518	8.41	
9590	13	5 1/4	.09189	11.95	
9635	45	4 3/4	.08309	3.74	
9665	30	4 1/2	.07870	2.36	
9763	98	4 1/4	.07431	7.28	
9837	74	3 1/2	.06116	4.53	
9885	48	3	.05241	2.52	321.39'
9920	35	3'	.05241	1.83	323.22'

Maximum Horizontal Displacement
of bottom of hole from top hole
location is 323.22'