

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-70

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☐ Fee ☐

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator TEXACO Inc.	8. Farm or Lease Name J. R. Phillips
3. Address of Operator P. O. Box 728, Hobbs, New Mexico 88240	9. Well No. 3
4. Location of Well UNIT LETTER <u>E</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>6</u> TOWNSHIP <u>20-S</u> RANGE <u>37-E</u> NMPM.	10. Field and Pool, or Wildcat Junice Monument Grayburg San Andres
11. Elevation (Show whether DF, RT, GR, etc.) 3576' (DF)	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/>

Add Perfs in San Andres

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. RIGGED UP. PULLED RODS AND PUMP. INSTALLED BOP. PULL TUBING.
2. SET CEMENT RETAINER @ 3615'. SQUEEZED PERFS 3628'-3662' W/100 SX CLASS H CEMENT CONTAINING 5% HALAD-9 AND FOLLOW W/75 SX CLASS H CEMENT CONTAINING 2% CACL.
3. PERFORATE 4 1/2" CASING W/2-JSPF @ 3442', 56', 70', 75', 82', 83', 85', 89', 90', 91', 3604', 06', 08', & 3610'.
4. SET PKR @ 3428'. ACIDIZE PERFS 3442'-- 3610' W/6500 GALS 20% NEFE ACID & 88 BALL SEALERS. FLUSH W/16 BBLs FRESH WATER.
5. INSTALL PUMPING EQUIPMENT. TEST AND PLACE ON PRODUCTION.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie W. Seay TITLE ASST DIST MGR DATE 7-23-84  
APPROVED BY Oil & Gas Inspector TITLE  DATE JUL 25 1984  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUL 24 1984

6-211  
NEWS OFFICE