iate

e of New Mexico

Form C-103

ししご

pies Energy, Minerals and Natural Resources Department Revised 1-1-89 office OIL CONSERVATION DIVISION CTI WELL API NO. 2040 Pacheco St. 30x 1980, Hobbs NM 88241-1980 30-025-05978 Santa Fe, NM 87505 5. Indicate Type of Lease J. Drawer DD, Artesia, NM 88210 FEE X STATE \square DISTRICT III 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" Bertha J. Barber (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: well WELL X OTHER 8. Well No. 2. Name of Operator 12 Cross Timbers Operating Company 9. Pool name or Wildcat 3. Address of Operator Monument Abo 3000 N. Garfield, Suite 175 Midland, Texas 79705 4. Well Location East 660 North Feet From The 330 Line Line and _ Feet From The Unit Letter 37E Lea **20S** County Range Township 10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR 3557 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: ALTERING CASING PLUG AND ABANDON REMEDIAL WORK PERFORM REMEDIAL WORK PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. CHANGE PLANS TEMPORARILY ABANDON CASING TEST AND CEMENT JOB PULL OR ALTER CASING OTHER: Recompletion to Monument Abo 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. MI completion unit. RU Baker Atlas Wedge wireline truck & ran GR/CCL log. Perf 12/18/98 - 1/28/99 Abo w/3-1/8" gun, 1 jspf from 7380-7264', total 28 holes. RD wireline truck. Acidized perfs w/2500 g. 15% NEFE HCl acid. Swbd perfs dry. Acidized w/15000 g. SXE acid plus additional 7500 g. 15% NEFE HCl acid. Swbd perfs dry. RU Baker Atlas wireline truck & perf'd 7190-7074' w/3-1/8" gun @ 1 jspf, total 29 holes. RD wireline truck. Acidized perfs w/2350 g. 15% NEFE HCl acid. Swbd perfs dry. Acidized w/15000 g, 15% SXE acid plus an additional 7500 g. 15% NEFE HCl acid. Swbd perfs dry. RU Baker Atlas wireline truck & perf'd Abo from 7008-6892' w/3-1/8" gun @ 1 jspf, total 26 holes. RD wireline truck. Acidized perfs w/1500 g. 15% NEFE HCl acid. Swbd perfs dry. Acidized perfs with an additional 3000 g. 15% NEFE HCl acid. Swbd perfs dry. TIH w/2-3/8" production tubing and landed @ 7436'. TIH w/rods and $2" \times 1 \cdot 1/2" \times 16'$ RHBC pump. Started well pumping. Prep to place on production test for completion data. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 3/10/99 тпье <u>Regulatory Tec</u>h DATE TELEPHONE NO. 915/682-8873 <u>Ja</u>nice Courtney TYPE OR PRINT NAME ORIGINAL

This space for State Use)

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY_