

NW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MICELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON <del>Repair 7" csg.</del> (Other) <del>Rem 5" Csg.</del>	

**FINAL COMPLETION**

January 20, 1955  
(Date)

Robbs, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

**THE OHIO OIL COMPANY**

(Company or Operator)

**W. E. Laughlin Lease**

(Lease)

**Harrell Smith**

(Contractor)

Well No. **3** in the **S<sup>1</sup>/<sub>4</sub>** **NE** **1/4** of Sec. **8**

T. **20-S**, R. **37-E**, NMPM, **Monument - Oil** Pool, **Law** County.  
**Monument - Gas**

The Dates of this work were as follows: **10-25-54 to 1-13-55**

Notice of intention to do the work (was) ~~was not~~ submitted on Form C-102 on **October 21, 1954**, 19\_\_\_\_  
(Cross out incorrect words)

and approval of the proposed plan (was) ~~was not~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Total Depth 3650'. Set bridge plug 3625'. Part 7" csg. 2530' with 4 jet shots, squeezed with 25000', held O.K. Rem 5" csg. to 3816' & cemented w/200 ss. PERF 3836'. Perf 5" csg. 3747-3804' & acidized w/3500 gals, no results. Perf. 3804-3818', sand fraced w/10,000 gals oil & 10,000' sand. Flowed 15 bbls oil per hr through 36/64" choke, from Monument oil zone. Set Baker Model "D" production packer at 3800'. Perf. 5" csg. 3196-3522, 3394-3452, 3327-3334, 3346-3362, 3370-3386, 3194-3210, 3254-3264, 3104-3120, 3136-3148 & 3154-3172'. Acidized w/3,000 gals with poor results. Sand fraced with 10,000 gals oil and 10,000' sand. Open flow potential test 20,000,000 c.f.g.d. from the Monument gas zone.

3747

Witnessed by **R. G. Howard**  
(Name)

**The Ohio Oil Company**  
(Company)

**Foreman**  
(Title)

Approved: **OIL CONSERVATION COMMISSION**

*S. J. Stanley*  
(Signature)

(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

ORIGINAL

SIGNED BY: **D. L. PROVINCE**

Name.....

Position..... **Superintendent**

Representing..... **The Ohio Oil Company**

Address..... **Box 2107, Robbs, New Mexico**

(Title)

(Date)