

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

FILE IN TRIPLICATE

OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

2040 Pacheco St.
Santa Fe, NM 87505

DISTRICT II
811 S. 1st Street, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd, Aztec, NM 87410

WELL API NO.	30-025-07649
5. Indicate Type of Lease	FED <input type="checkbox"/> STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	SOUTH HOBBS (G/SA) UNIT
8. Well No.	8
9. Pool name or Wildcat	HOBBS (G/SA)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101 FOR SUCH PROPOSALS.)	
1. Type of Well:	Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> INJECTOR (SHUT IN)
2. Name of Operator	OCCIDENTAL PERMIAN LTD.
3. Address of Operator	1017 W. Stanolind Rd., HOBBS, NM 88240 505/397-8200
4. Well Location	Unit Letter <u>D</u> : <u>330</u> Feet From The <u>NORTH</u> Line and <u>933</u> Feet From The <u>WEST</u> Line Section <u>6</u> Township <u>19S</u> Range <u>38E</u> NMPM LEA County
10. Elevation (Show whether DF, RKB, RT GR, etc.) 3644' GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG & ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work)
SEE RULE 1103.

Notify the NMOCD 24 hr before job. (393-6161)

Well is a TA'd well. CIBP set @4010'.
Spot 35 sxs cmt on CIBP @4010'. TOC @3975'.
Circ Mud Gel from 3975' to 2650'.
Spot cmt from 2650' to 2550'. Bot of Anhy @2600'.
Circ Mud Gel from 2550' to 1650'.
Spot cmt from 1650' to 1550'. Top of Anhy @1600'.
Circ Mud Gel from 1550' to 400'.
Spot cmt from 400' to 275'. Bot of 8-5/8" csg @322'.
Circ Mud Gel from 275' to 60'.
Spot cmt from 60' to surface.
Install dry hole marker. SHU 008, UL - D, 330 FNL, 933 FWL. Sec - 6, T-19S, R-38E 8-9-02

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robert Gilbert TITLE SR. ENGR. TECH DATE 08/09/2002
TYPE OR PRINT NAME Robert Gilbert TELEPHONE NO. 505/397-8206

(This space for State Use)

APPROVED BY Johnny Robinson TITLE COMPLIANCE OFFICER DATE DEC 10 2002
CONDITIONS OF APPROVAL IF ANY

GWW

J
C
S