COPY TO O. C. C.

Form 9-331 Dec. 1973

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	Budget Bureau No. 42-R1424
Γ	5. LEASE
١	NM-16835
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-	7. UNIT AGREEMENT NAME
ŀ	8. FARM OR LEASE NAME
-	Federal AG Com 9. WELL NO.
1	1
١	10. FIELD OR WILDCAT NAME
-	Wildcat West Osudo Morrow
	11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA
	14-20-35
	12. COUNTY OR PARISH 13. STATE
	Lea NM
	14. API NO.
	3695.2 RDB
	15 ELEVATIONS (SHOW DE KDB. AND WE

Form Approved.

dededione of	·		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME		
1. oil gas well other 2. NAME OF OPERATOR Amoco Production Company 3. ADDRESS OF OPERATOR P. O. Box 68 Hobbs, NM 88240 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1980' FNL & 1980' FWL, Sec. 14 AT TOP PROD. INTERVAL: AT TOTAL DEPTH: (Unit F, SE/4, NW/4) 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	Federal AG Com 9. WELL NO. 1 10. FIELD OR WILDCAT NAME Wildcat West Osudo Morrow 11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA 14-20-35 12. COUNTY OR PARISH Lea 14. API NO. 3695.2 RDB 15. ELEVATIONS (SHOW DF, KDB, AND WD)		
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)	(NOTE: Report results of multiple completion or zon change on Form 9–330.)		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to a TD of 11617' and ran 75/8" casing set at 11617'. DV tool set at 9013'. Cemented first stage with 925 SX lite cement and 250 Sx class H cement. Opened DV tool. Top of cement found by temp survey at 6100'. Will drill to TD and if logs show possible commercial production will perforate and cement TD and if logs show possible to 6-1 behing 7-5/8". Reduced hole to 6-1 ECESUMPED ling.

APR 11 1980

U. S. GEOLOGICAL SURVEY HOBBS, NEW MEXICO

Subsurface Safety Valve: M					Set @ Ft.
18. I hereby certify that the	foregoing is tr	ue and correct тітье <u>Admin.</u>	Analyst	DATE 4-	ACCEPTED FOR RECORD
APPROVED BY		(This space for Federal o	r State office use		APR 1 1 1980
conditions of approval. 0+4-USGS-H	if any: 1-Hou	1-Susp	1-BD	1-Supe	U. S. GEOLOGICAL SURVEY