

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-105
Revised 1-1-89

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.

30-025-33019

5. Indicate Type Of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐

b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RESVR ☐ OTHER ☐

2. Name of Operator
Amerada Hess Corporation

7. Lease Name or Unit Agreement Name
North Monument Grayburg S/A Unit
Well #2222

3. Address of Operator
P.O. Drawer D, Monument NM 88265

8. Well No.
284
9. Pool name or Wildcat
Eunice Monument G/SA

4. Well Location
Unit Letter F : 2650' Feet From The North Line and 2630' Feet From The West Line

Section 4 Township 20S Range 37E NMPM Lea County

10. Date Spudded 7/13/95 11. Date T.D. Reached 7/25/95 12. Date Compl.(Ready to Prod.) 10/25/95 13. Elevations(DF & RKB, RT, GR, etc.) 3557' GL 14. Elev. Casinghead

15. Total Depth 4042' 16. Plug Back T.D. 3908' 17. If Multiple Compl. How Many Zones? 18. Intervals Drilled By Rotary Tools Cable Tools X

19. Producing Interval(s), of this completion - Top, Bottom, Name OH 3703-3908' Grayburg San Andres 20. Was Directional Survey Made Yes

21. Type Electric and Other Logs Run DITE/GR/SP, LDT/CNL/GR/COLP, RFT 22. Was Well Cored Yes

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3#	442'	12 1/4"	225 sx CL C	
7"	20#	3703'	8 3/4"	600 sx C1 C and	
				300 sx C1 H	

24. LINER RECORD				25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET
					2 7/8"	3884'

26. Perforation record (interval, size, and number)	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
	3703-3908'	10,000 gals 15% NEEF DI acid
		w/1.5% DP-77 MX micellar solvent

28. PRODUCTION

Date First Production 10/25/95 Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping - 2 1/2" x 1 1/2" RHBC Rod Pump Well Status (Prod. or Shut-in) Producing

Date of Test 11/14/95 Hours Tested 24 Choke Size Prod'n For Test Period Oil - Bbl. 11 Gas - MCF 19 Water - Bbl. 53 Gas - Oil Ratio 1727

Flow Tubing Press. Casing Pressure Calculated 24-Hour Rate Oil - Bbl. Gas - MCF Water - Bbl. Oil Gravity - API (Corr.)

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold Test Witnessed By

30. List Attachments

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature Karen Friday Printed Name Karen Friday Title Production Tech Date 11-30-95

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including ~~drill-stem~~ tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

Southeastern New Mexico

Northeastern New Mexico

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

No. 1, from	to	No. 3, from	to
No. 2, from	to	No. 4, from	to

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet

(Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology
0	1246	1246	Red Beds
1246	1329	83	Anhydrite
1329	2520	1191	Salt
2520	3396	876	Dolomite, Anhydrite
3396	3677	281	Sand, Dolomite, Anhydrite
3677	4042	365	Dolomite
From	To	Thickness in Feet	Lithology