

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

|                                      |  |   |  |                                      |          |
|--------------------------------------|--|---|--|--------------------------------------|----------|
| NOTICE OF INTENTION TO CHANGE PLANS  |  | NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL |  | NOTICE OF INTENTION TO DRILL DEEPER  | <b>X</b> |
| NOTICE OF INTENTION TO PLUG WELL     |  | NOTICE OF INTENTION TO PLUG BACK                |  | NOTICE OF INTENTION TO SET LINER     |          |
| NOTICE OF INTENTION TO SQUEEZE       |  | NOTICE OF INTENTION TO ACIDIZE                  |  | NOTICE OF INTENTION TO SHOOT (Nitro) |          |
| NOTICE OF INTENTION TO GUN PERFORATE |  | NOTICE OF INTENTION (OTHER)                     |  | NOTICE OF INTENTION (OTHER)          |          |

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

September 29, 1954  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Eurice King

Gulf Oil Corporation  
(Company or Operator)

Well No. 16 in A  
(Unit)

NE  $\frac{1}{4}$  NE  $\frac{1}{4}$  of Sec. 28, T. 21-S, R. 37-E, NMPM., Hare Pool

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to drill deeper and recomplete as follows:

1. Drill from Plugged Back Total Depth 7555' to 7720'.
2. Run Schlumberger ES and microlog surveys.
3. Underream open hole to 8-1/4".
4. Run approximately 160' 5-1/2" OD 17# Gr J-55 SS casing to set from 7560' to 7720'.
5. Cement liner with 4' Gel cement.
6. Clean out to float shoe.
7. Perforate liner opposite Connell Sand from interpretation of logs.
8. Run hookwall packer and hydraulic holddown. Test Connell Sand and treat with 3000 gallons Fracture if warranted.
9. Pull packer and produce McKee and Connell Sands together.

Approved....., 19.....  
Except as follows:

Gulf Oil Corporation  
Company or Operator

By.....

Position..... Area Supt. of Prod.  
Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Name..... Gulf Oil Corporation

Title.....

Address..... Box 2167, Hobbs, N. M.