

JIL CONSERVATION DIVISIO..

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name Central Drinkard Un
2. Name of Operator Chevron U.S.A. Inc.	8. Farm or Lease Name
3. Address of Operator P.O. Box 670, Hobbs, NM 88240	9. Well No. 128
4. Location of Well UNIT LETTER <u>B</u> <u>810</u> FEET FROM THE <u>North</u> LINE AND <u>2180</u> FEET FROM THE <u>East</u> LINE, SECTION <u>33</u> TOWNSHIP <u>21S</u> RANGE <u>37E</u> N.M.P.M.	10. Field and Pool, or Wildcat Drinkard
11. Elevation (Show whether DF, RT, GR, etc.) 3459	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK

TEMPORARILY ABANDON

PULL OR ALTER CASING

OTHER _____

PLUG AND ABANDON

CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIATION WORK

COMMENCE DRILLING OPNS.

CASING TEST AND CEMENT JOB

OTHER sqz, perf,

ALTERING CASING

PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Work performed 4-13-88 thru 4-21-88 TD: 7644 PB: 6700

POOH w/ production equipment. Pmp tbg cap. Set cmt retainer, test tbg to 3000psi, load and test annulus to 500psi, estab. inj rate of 1 1/2 bpm at 900psi, mix and pump 200sx Cl H cmt, sqz perfs 6469-6520 w/2300psi. Rev out 4bbbls. Estb. circ, drlg 3'cmt, drill cmt rtrn 6374-6408 (cmt green), WOC 18 hrs. Drlg cmt 6408 - 6565, c/o to 6700. Displace hole w/ CBW. Perf 6535-6548-6556-6561-6573-6587 w/4" guns loaded 2 SPF, 180° phase, Acdize perfs 6585 - 6587, w/ 4100 gallons 15% NEFE HCL. Swab. TIH, tag sand at 6501'. Wash sand 6510 0 6700, PBT. RIH w/ 2 7/8" , ND BOP, NU WH, TAC at 6422, SN at 6553', 2 7/8" J-55, 8rd tbg at 6589'. Space out, hang on, Test pmp, ok. Turn over to production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED M. E. Stein TITLE Staff Drlg. Engr DATE May 5, 1988

APPROVED BY Jerry [Signature] TITLE DISTRICT 1 SUPERVISOR DATE MAY 7 1988

CONDITIONS OF APPROVAL, IF ANY: