

X									

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

Stanolind Oil and Gas Company State "C" Tract 13
(Company or Operator) (Lease)

Well No. 8, in NW 1/4 of NW 1/4, of Sec. 36, T. 21-S, R. 37-E, NMPM.
Drinkard (oil) Tubb (gas) Pool, Lea County.

Well is 990 feet from North line and 660 feet from West line
of Section 36. If State Land the Oil and Gas Lease No. is B-1557

Drilling Commenced 4-27, 19.55 Drilling was Completed 6-5, 19.55

Name of Drilling Contractor Lee Drilling Company

Address Philtower Building, Tulsa, Oklahoma

Elevation above sea level at Top of Tubing Head 3379 The information given is to be kept confidential until
Not Confidential, 19.

OIL SANDS OR ZONES

No. 1, from 6030 to 6260 No. 4, from to
No. 2, from 6522 to 6596 No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8"	36#	New	298	Float			
9-5/8"	32-20	New	2887	Float			
7	20-23	New	6638	Float			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2	13-3/8	310	300	Howco Plug		
12-1/4	9-5/8	2900	1st - 175 2nd - 150	Howco Plug		
8-3/4	7	6600	150	Howco Plug		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

5500 gallon 15% regular

15000 gallon 15% regular

Result of Production Stimulation See Reverse Side

Depth Cleaned Out

AD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 6600 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 6-5, 19.55

* OIL WELL: The production during the first 24 hours was 85.6 barrels of liquid of which 100 was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 36°

* GAS WELL: The production during the first 24 hours was 2482 M.C.F. plus 1.8 barrels of liquid Hydrocarbon. Shut in Pressure 2175 lbs.

Length of Time Shut in 18 hrs.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta 5165	T.	T. Morrison
T. Drinkard 6357	T.	T. Penn.
T. Tubbs "Marker" 6052	T.	T.
T. Abo	T.	T.
T. Penn.	T.	T.
T. Miss.	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	312	312	Red Bed				
312	1000	688	Red Bed - Shells				
1000	1323	323	Anhy. - Gyp				
1323	1595	272	Anhy.				
1595	2575	980	Anhy. - Salt				
2575	2900	325	Anhy. - Gyp.				
2900	3136	236	Anhy.				
3136	3884	748	Anhy. - Lime				
3884	6600	2716	Lime				
* This well dually-completed gas-oil. Drinkard oil portion completed 6/5/55 Tubbs gas portion completed 7/4/55.							

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

July 28, 1955

(Date)

Company or Operator Stanolind Oil and Gas Company

Address Box 68 Hobbs, New Mexico

Original Signed by

Name RALPH L. HENDRICKSON

Position or Title Field Superintendent