

RECEIVED

JUL 11 1951

OIL CONSERVATION COMMISSION
HOBBS OFFICE

OIL CONSERVATION COMMISSION ON
SANTA FE, NEW MEXICO
Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

July 10, 1951

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil & Gas Co. - K. H. Coll Well No. 1 in the

Company or Operator

NW/4

of Sec. 2

Lease 20-5

R. 38-E

N. M. P. M.

Wildcat

Field

Lea

County.

The dates of this work were as follows: June 3-12, 1951

Notice of intention to do the work was (was not) submitted on Form C-102 on June 2 19 51

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The following procedure was used to abandon subject well:

25 sack cement plugs were placed at the following intervals:

7180-7300; 6840-6950; 5490-5600; 4240-4350; and 3875 to 3765. Shot off 7-5/8" casing at 2585' and pulled 2620'. Spotted 30 sack plug from 2540-2617; 1618-1680; and 15 sack plug from 26' to surface. All intervals between plugs filled with heavy mud laden fluid. A 4" pipe marker was erected to extend 5' above ground level and location leveled.

T. S. Holden

Stanolind Oil & Gas Company

Hd. Rsbt.

Witnessed by

Name

Company

Title

Subscribed and sworn before me this

10th day of July 19 51

[Signature]
Notary Public

My Commission Expires November 16, 1954

My commission expires

I hereby swear or affirm that the information given above is true and correct.

Name *[Signature]*

Position Production Foreman

Representing Stanolind Oil & Gas Company
Company or Operator

Address Box "F" - Hobbs, New Mexico

Remarks:

APPROVED
JUL 12 1951
Date

[Signature]
Name
Oil & Gas Inspector