NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

RECEIVED

Address Box 97, Hobbs, New Mexico

MISCELLANEOUS REPORTS ON WELLS

ٳ

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the profit precified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing that of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature	of Report by Checkin	ng Belov	v		
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON OF CASING	RESULT OF TEST SHUT-OFF	x	REPORT ON REPAIRING WEI	LL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON OPERATION	RECOMPLETION		REPORT ON (Other)		
		July 1, 1952				New Mexalo
		(Date)	••••••		(Place)	
Following is a report on the work	done and the results of	btained under the hea	ding not	ed above at the		
Cities Service	Cil Company		·····	(Leage)	rers	
	Company	, Well No	•••••	in the NE 1/4 SI		c 7 ,
г. 206 , к. 38Е , ммрм., Un		Pool			Lea	County.
The Dates of this work were as follows:	•					
The Dates of this work were as tolows:	9417 11 17/2		• • • • • • • • • • • • • • • • • • • •			
Notice of intention to do the work (was) (was not submitted or	n Form C-102 on		July 1		, ₁₉ 52
DETAI	LED ACCOUNT OF W			•		
	8-5/8" casing was 1952. Cement wanters and applications	as cemented at as allowed to ed 1000# press	3701 set 48 ure ar	and plug was hours then ni	lppled up	•
TD 3701 Lime. The at 7:30 AM July 29, put on blowout preve	8-5/8" casing was 1952. Cement wanters and applications	as cemented at as allowed to ed 1000# press	3701 set 48 ure ar	and plug was hours then ni	lppled up	•
TD 3701 Lime. The at 7:30 AM July 29, put on blowout preve	8-5/8" casing was 1952. Cement wanters and applications	as cemented at as allowed to ed 1000# press	3701 set 48 ure ar	and plug was hours then ni	lppled up	•
TD 3701 Lime. The at 7:30 AM July 29, put on blowout preve	8-5/8" casing was 1952. Cement wanters and applications	as cemented at as allowed to ed 1000# press	3701 set 48 ure ar	and plug was hours then ni	lppled up	•
TD 3701 Lime. The at 7:30 AM July 29, put on blowout preve	8-5/8" casing was 1952. Cement wanters and applications	as cemented at as allowed to ed 1000# press	3701 set 48 ure ar	and plug was hours then ni	lppled up	•
TD 3701' Lime. The at 7:30 AM July 29, put on blowout preve	8-5/8" casing was 1952. Cement wanters and applications	as cemented at as allowed to ed 1000# press	3701 set 48 ure ar	and plug was hours then ni	lppled up	•
TD 3701 Lime. The at 7:30 AM July 29, put on blowout preve	8-5/8" casing was 1952. Cement was nters and appliant the saure held and	as cemented at as allowed to ed 1000# press	3701 set 48 ure ar ng cen	and plug was hours then nind held pressurent. Product:	lppled up	ing
TD 3701' Lime. The at 7:30 AM July 29, put on blowout preve for 30 minutes. Pre	8-5/8" casing was 1952. Cement was and appliant the same held and second control of the same held and	as cemented at as allowed to ed 1000# press started drilli:	3701 set 48 ure ar ng cen	and plug was hours then nind held pressurement. Product:	lppled up re on cas	ing
TD 3701 Lime. The at 7:30 AM July 29, put on blowout preve for 30 minutes. Pre	8-5/8" casing was 1952. Cement was and appliant the same held and second control of the same held and	ies Service Oi (Company) I hereby certo the best o	3701 set 48 ure are ng cent	and plug was hours then nind held pressurement. Product:	Lon Forem	ing

(Date)