

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE

Grid for well location with a dot in the second row, second column.

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (T). SUBMIT IN TRIPLICATE.

AREA 640 ACRES LOCATE WELL CORRECTLY

Gulf Oil Corporation

Tulsa, Oklahoma.

Company or Operator

Address

J. H. Day

Well No. 1

NE NE SW

of Sec. 8

T. 22S

Lease

R. 36E

N. M. P. M.

Runice

1961

Lee

County.

Well is 330

feet south of the North line and

330

feet west of the East line of

NE NE SW

If State land the oil and gas lease is No.

Assignment No.

If patented land the owner is

Address

If Government land the permittee is

Address

The Lessee is

Gulf Oil Corporation

Address

Tulsa, Oklahoma.

Drilling commenced

12-8-56

is

Drilling was completed

1-18-57

Name of drilling contractor

Lee Drig.

Address

Tulsa, Oklahoma.

Elevation above sea level at top of casing

5562

feet.

The information given is to be kept confidential until

19

OIL SANDS OR ZONES

No. 1, from

5570

to

5695

No. 4, from

to

No. 2, from

5695

to

5851

No. 5, from

to

No. 3, from

to

No. 6, from

to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from

Rotary hole

to

feet.

No. 2, from

to

feet.

No. 3, from

to

feet.

No. 4, from

to

feet.

CASING RECORD

Table with columns: SIZE, WEIGHT PER FOOT, THREADS PER INCH, MAKE, AMOUNT, KIND OF SHOE, CUT & FILLED FROM, PERFORATED FROM TO, PURPOSE. Rows include 15" OD, 9-5/8, and 7" casing.

MUDDING AND CEMENTING RECORD

Table with columns: SIZE OF HOLE, SIZE OF CASING, WHERE SET, NO. SACKS OF CEMENT, METHOD USED, MUD GRAVITY, AMOUNT OF MUD USED. Rows include 17 1/2, 12 1/2, and 8-5/4 casing sizes.

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

Table with columns: SIZE, SHELL USED, EXPLOSIVE OR CHEMICAL USED, QUANTITY, DATE, DEPTH SHOT OR TREATED, DEPTH CLEANED OUT.

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 5851 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing February 1st, 19 57
The production of the first 24 hours was 484 barrels of fluid of which % was oil;
emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas.
Rock pressure, lbs. per sq. in.

EMPLOYEES

Driller
Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 4th day of March, 19 57
Notary Public.
Tulsa, Oklahoma March 4th, 1957
Name: [Signature]
Position: General Superintendent
Representing: Gulf Oil Corporation
Address: Tulsa, Oklahoma.

FORMATION RECORD

30. 11. 1917

FROM	TO	THICKNESS IN FEET	FORMATION
0'	40'		Sand
	177		Sand, red rock and red bed
	225		Red bed and shells
	257		Hard sand
	270		Red rock and Gyp
	285		Red Rock
	325		Red bed
	389		Red rock
	425		Red rock, gyp and red bed
	550		Red bed, red rock and sand
	616		Red bed and red rock
	721		Red rock, sand, shells and red bed
	804		Red rock and red bed
	886		Red rock, anhydrite and red bed
	1060		Red rock and hard sand
	1161		Red rock, red bed and hard sand
	1258		Anhydrite and red rock
	1590		Red rock
	1659		Anhydrite
	1678		Anhydrite and Gyp
	1682		Anhydrite
	1858		Salt, Anhydrite and red rock
	1910		Salt and Anhydrite
	2010		Salt, anhydrite and shells
	2775		Salt and shells
	2808		Salt and Anhydrite
	2940		Salt, Gyp and Potash
	3050		Salt, shells and Gyp
	3154		Salt, Gyp and Potash
	3190		Salt and shells
	3215		Anhydrite
	3255		Anhydrite and Brown lime
	3290		Anhydrite and Gyp
	3372		Anhydrite, Gyp and lime
	3390		Brown lime
	3467		Lime and Sand
	3775		Brown lime
	3851		Brown lime
			Tops: Anhydrite 1590'
			Top of Salt 1682
			Base of Salt 3189
			Brown Lime 3245
			Ransay 3420
			Upper San Andres 3570
			Cooper Terry 3685
			Fay 3765