

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-08906
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil & Gas Lease No.	A-2614
7. Lease Name or Unit Agreement Name	ARROWHEAD GRAYBURG
8. Well No.	236
9. Pool name or Wildcat	ARROWHEAD/ GRAYBURG

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:	OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator	CHEVRON U.S.A. INC.
3. Address of Operator	P.O. BOX 1150 MIDLAND, TX 79702 ATTN: P.R. MATTHEWS
4. Well Location	

Unit Letter J : 2310 Feet From The SOUTH Line and 1650 Feet From The EAST Line

Section 13 Township 22S Range 36E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3463 GE

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: DEEPEN, PERF, LOG, ACDZ. ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU, POOH W/PROD. EQUIP. TIH W 4 1/2" PKR., ISOLATE CSG. LEAK AT 503-565.
SET CIBP AT 3680, RUN VERTILOG 3678-SURFACE. CAP CIBP W/35' CMT(2 SXS.) PERF 4
SQZ. HOLES AT 930'. SET CIGR AT 875', MIX AND PUMP 180 SXS. CMT. DRLG CMT. 238-875.
TST CSG TO 300 PSI- OK. DRILL CIGR AT 875' CONTINUE DRLG TO 935' TST/CSG TO
300 PSI- LEAKED OFF. FOUND HOLE ON TOP OF 4" CSG. REPAIRED LEAK. DRILL CMT. AND
CIBP 3645-3752. SET PKR. AT 3514, PUMPED 25 SXS. CMT. DRILL CMT. PLUG AND FORMATION
3658-3890. LOG HOLE: GR-NEUTRON-CAL-CCL. DRLG 3890-3910. PERF 3626-3706 W/HYPER
JET II, 2 JHPF, 180 DEG. PSHD., 3 7/8" GUNS, TOTAL 68 HOLES.
ACDZ 3626-3706 W /1200 GALS. 15% NEFE. ACDZ 3724-3910 W/ 1500 GALS. 15% NEFE.
MADE SEVERAL SWB/TST. TIH W/ PROD. EQUIP. EOT AT 3882'.
RDMO, RETURN TO PRODUCTION.

WORK STARTED 7-15-91 WORK ENDED 8-6-91.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE P.R. Matthews TITLE TECHNICAL ASSISTANT DATE 8-7-91
TYPE OR PRINT NAME P.R. MATTHEWS TELEPHONE NO. 687-7812

(This space for State Use)

APPROVED BY DATE AUG 09 1991
CONDITIONS OF APPROVAL, IF ANY: