

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0557686
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR
Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2130' FSL & 1980' FEL OF SEC. 23

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
SEMU PENN

9. WELL NO.
95

10. FIELD AND POOL, OR WILDCAT
CASS PENN

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 23, T-20S, R-37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3532' DF

12. COUNTY OR PARISH 13. STATE
LEA N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data.

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) SET PROD. LINER

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 95 sts. 5 1/2" 17# K-55 LT&C Casing. Set shoe @ 7754' w/top of liner hanger @ 3805'. Cemented w/775' sks Class "C" cmt. Plug down 12-30-74. Waited on compl. rig till 1-17-75. Ran 4 3/4" bit & scraper, found no cement on top of liner. Set Retr. Pkr. @ 3701'. Pmpd 75 sks. Class "C" cmt below pkr. WOC 48 hrs. Drilled out cmt 3802'-3810'. Tested top of liner w/1100 psi for 30 min. Held Ok. Preparing to resume drly. oper 1-22-75.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

SR. ANALYST

DATE

1-23-75

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
DATE

JAN 27 1975

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

USGS-5, NMPU-4, File

*See Instructions on Reverse Side