Form 3160-3 (July 1992)

12½"

<u>7</u> 7/8"

J-55

J - 55

8_5/8"

5½"

N. M. C. CONS. BENEVIOUS

TED STATES NEW Cother Instructions

OMB NO. 1004-0136
Expires: February 28, 1995

CENT LEASE DESIGNATION AND SERIAL NO.

FORM APPROVED

BUREAU OF LAND MANAGEMENT 930 RECEIVED LEASE DE

APPL	ICATION FO	R PERMIT T	O DRIL	L OR DE	EPEN.	D 12	97. IF INDIAN, ALLOTTI	E OR TRIBE NAME
1a. TYPE OF WORK	RILL X	DEEPE				BL	7. UNIT AGREEMENT	NAMB
b. TYPE OF WELL OIL WELL	GAS OTH	r.		INGLE E	MULTAP	eswif-	16. FARM OR LEASE NAME W	ELL NO.
2. NAME OF OPERATOR POGO PRODUCII	NG COMPANY	(RICHAR	D WRIGH	T)			E. LIVINGSTON 9. AT WELL NO.	RIDGE UNIT
3. ADDRESS AND TELEPHONE NO. 10340 M	IDLAND, TEXAS	79702	Phone 9	15-682-68	322		30-025 10. FIELD AND POOL,	-34/70 OR WILDCAT
4. LOCATION OF WELL (At SULLACE 330' FSL & 1 At proposed prod. 20	650' FEL SEC.				ents.*)		E. LIVINGSTON 11. SEC., T. B., M., OB AND SURVEY OR A SEC. 7 T22S	BLE.
14. DISTANCE IN MILES Approximatel	AND DIRECTION FROM y 30 miles Ea						12. COUNTY OR PARISH	NM
13. DISTANCE FROM PROI LOCATION TO NEARE: PROPERTY OR LEASE (Also to nearest dr	ST	1500'	1	OF ACRES IN	LEASE		OF ACRES ASSIGNED HIS WELL 4	0
18. DISTANCE FROM PRO TO NEAREST WELL. OR APPLIED FOR, ON TI	DRILLING, COMPLETED.	660'		400 T		1	ROTARY	
21. ELEVATIONS (Show w)	bether DF, RT, GR, et	e.)					22. APPROX. DATE WO	BE WILL START
		3686 '	GR.				As soon as ap	proved
SECRETA	RY'S POT ASH	PROPOSED (ASING AND	COARLS	BADRO	ONTRE	LLED WATER	BASIN
SIZE OF HOLE	ORADE, SIZE OF CASING	WEIGHT P	ER FOOT	SETTING D	BPTH .		QUANTITY OF CEME?	(T

40 T

1500 Sx.

650'

7400'

1. Drill 25" hole to 40'. Set 40' of 20" conductor and cement to surface with Redi-mix.

NA

24

17 & 15.5

- 2. Drill 12½" hole to 650'. Run and set 650' of 8 5/8" J-55 24# 8-R ST&C casing. Cement with 300 Sx. of Halco Light, tail in with 200 Sx. of Class "C" + 2% CaCl, circulate cement to surface.
- 3. Drill 7 7/8" hole to 7400'. Run and set 7400' of 5½" J-55 17 & 15.5 # 8-R ST&C casing as follows: 1000' of 17# & 6400' of 15.5# all J-55 ST&C casing. Cement with 1000 Sx. of Halco Light + additives, tail in with 500 Sx. of Premium Plus cement + additives. Circulate cement to surface.

SPECIAL STIPULATIONS

GNED JOSET James TITI	.eAgent	09/11/97 C
This space for Federal or State office use)		

*See Instructions On Reverse Side