
OIL CONSERVATION COMMISSION NEW MEXICO

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES



Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained See additional instructions in the Rules and Regulations of the Commission

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X NOTICE OF INTENTION TO SHOOT CHEMICALLY TREAT WELL	OR
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OTHERWISE ALTER CASING	OR
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG V	WELL.
NOTICE OF INTENTION TO DEEPEN WELL		
иол	DO SERVICIONE	
НОВ	BS, NEW MEXICO FEBRUARY	27, 194
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen:		
Following is a notice of intention to do certain work		
STANOLIND OIL & GAS CO. SOUTHLA Company or Operator Lease	TO ROYALTY CO. A Well No. 3	inSE
of Sec. 4, T. 21S, R. 37	, N. M. P. M., DRINKARD	F
County.		
FULL DETAILS OF I	PROPOSED PLAN OF WORK	
	ES AND REGULATIONS OF THE COMMI	CCION
sacks, to be used as surface stri		ut off
sacks, to be used as surface structure be tested as follows: Pressure of 1000# will be built used in built up and held for 30 minuilling operations will be resumed.	ing. At this time casing shoup and held for 30 minutes alled, and a pressure of 100 atcs. If this test, too, i	ut off and if 00#
<pre>sacks, to be used as surface str: be tested as follows: Pressure of 1000# will be built u st is OK, cement plug will be dr: ain built up and held for 30 minu</pre>	ing. At this time casing shoup and held for 30 minutes alled, and a pressure of 100 atcs. If this test, too, i	ut off and if 00#
<pre>sacks, to be used as surface str: be tested as follows: Pressure of 1000# will be built u st is OK, cement plug will be dr: ain built up and held for 30 minu</pre>	p and held for 30 minutes alled, and a pressure of 10 atcs. If this test, too, i	ut off and if OO# s OK,
sacks, to be used as surface stribe tested as follows: Pressure of 1000# will be built ust is OK, cement plug will be driain built up and held for 30 minuilling operations will be resumed. Approved	ing. At this time casing shoup and held for 30 minutes alled, and a pressure of 100 atcs. If this test, too, it.	ut off and if OO# s OK,
sacks, to be used as surface stribe tested as follows: Pressure of 1000# will be built ust is OK, cement plug will be driain built up and held for 30 minuilling operations will be resumed. Approved	STANDLIND OIL & Company or Operator By Position FIELD SUPT.	and if OO# s OK,
sacks, to be used as surface stribe tested as follows: Pressure of 1000# will be built a st is 0K, cement plug will be driain built up and held for 30 minuilling operations will be resumed. Approved	STANOLIND OIL & Company or Operator By Lacott Neutuck Position FILD SUPT. Send communications regarding Name RALPH L. HENDRICK	and if OO# s OK,