

DUPLICATE

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 031743 (b)
Unit N.M.F.U.

RECEIVED

AUG 22 1951

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<input type="checkbox"/>		

**WATER CONSERVATION COMMISSION
HOBBS OFFICE**

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

W. C. Hawk B-3 No. 1-S

Hobbs, New Mexico

August 16, 1951

Well No. 1-S is located 810 ft. from XXX line and 660 ft. from E line of sec. 3

SE/4 Sec. 3
(1/4 Sec. and Sec. No.)

21-S
(Twp.)

37-E
(Range)

N.M.P.M.
(Meridian)

Wildest
(Field)

Lea

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

ILLEGIBLE

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well at the above location to a total depth of approximately 7800' with rotary tools, in an attempt to obtain commercial production in the Simpson. All casing points will be cemented in accordance with approved methods of the U.S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing pattern: 10 3/4" casing to be set at approximately 250' and cemented with 250 sacks, cement to be circulated; 7 5/8" casing to be set at approximately 3150' and cemented with 990 sacks cement, or sufficient cement to protect the salt section as determined by survey; 5 1/2" casing to be set at total depth and cemented with 550 sacks cement as determined by survey, and to be perforated opposite the pay zone.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box CC

Hobbs, New Mexico

By [Signature]

Title Dist. Superintendent