

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	<input checked="" type="checkbox"/>
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

May 7, 1953

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil and Gas Company

(Company or Operator)

State C Tract 12

(Lease)

None

(Contractor)

Well No. 7 in the NW 1/4 NW 1/4 of Sec. 16

T. 21-S, R. 37-E, NMPM., Drinkard Pool, Lea County.

The Dates of this work were as follows: April 20-27, 1953

Notice of intention to do the work (was) ~~was not~~ submitted on Form C-102 on April 16, 1953

(Cross out incorrect words)

and approval of the proposed plan (was) ~~was not~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Results of work are detailed on the sheet attached to this form.

Witnessed by T. J. Thigpen Stanolind Oil and Gas Company Farm Boss

(Name)

(Company)

(Title)

Approved:

OIL CONSERVATION COMMISSION

Ray Garhrey

(Name)

& Gas Inspector

(Title)

MAY 8 1953

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Field Superintendent

Representing Stanolind Oil and Gas Company

Address Box 68, Hobbs, New Mexico

WELL REMEDIAL REPORT
NEW MEXICO OIL & GAS ENGINEERING COMMITTEE
BOX 127 HOBBS, NEW MEXICO

Company Stanolind Oil and Gas Company Address Box 68, Hobbs, N. M. Date May 7, 1953
Lease State C Tract 12 Well # 7 Unit D Sec. 16 T 21-s R 37-E Pool Drinkard

NATURE OF WORKOVER

Drill Deeper Cement plugback Plastic plugback Set Liner
Cement squeeze Plastic squeeze Set Packer Acidize x Shoot Perforate x

FOR PURPOSE OF

Increase production, Oil x Gas Shut off water Shut off gas

RESULTS SUMMARY

Complete success x Partial success Failure

DATE

Workover started April 20, 1953 Completed April 27, 1953

WELL DATA

D.F. elev. 3499 Completion date 7/27/49 Prod. formation Drinkard

Oil String 5-1/2 inch pipe set at 6629'

Depth of hole before 6690' After 6690'

Formation packer set at 6625 with perforations above x below

 inch liner set. Top Bottom Cemented w. sax,

and perforated with holes from to

Section squeezed from to with sacks cement or

 gallons plastic. Maximum pressure used P.S.I.

INSTRUMENTS RUN IN CONJUNCTION WITH OR PRIOR TO WORKOVER

Temperature bomb Electric log Dowell pilot Gamma ray
Water witch Hole Caliper Dia-log Other Lane Wells, collar locator

RESULTS DETAIL

	BEFORE	AFTER
Oil production Bbls./day	<u>25</u>	<u>70</u>
Water Production Bbls./day	<u>5</u>	<u>16</u>
Gas Production M.C.F./day	<u>197</u>	<u>792</u>
Gas oil ratio	<u>8177</u>	<u>1132</u>

REMARKS: Perforated interval from 6692 to 6618' w/a shaped charges per foot.

Washed perforations with 500 gallons 15% acid and acidized formation with 2000 gal
15% acid.

