

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
BELCO PETROLEUM CORPORATION
3. ADDRESS OF OPERATOR
10,000 Old Katy Road #100, Houston, TX 77055
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: **1980' FSL, 660' FWL**
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED
JUN 21 1978

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
HOBBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/6/78	Moved in casing pulling unit.		
6/7/78	POH w/2-3/8" tbq; installed BOP.		
6/8/78	Set cement retainer @ 13,855'; sqzd perfs @ 13,958-13,993' w/50 sx Class "H"; spotted 35 sx Class "H" from 11,450-11,756'.		
6/9/78	T.I. H. w/csg. cutter.	6/20/78	Rec 10,175' 5 1/2" csg; spotted 35 sx cmt plug 10,245-10,145'.
6/10/78	Unable to get below 8490'.	6/21/78	Spotted 60 sx Class "C"; cmt plug from 5170-5060'; 6 hr WOC; went in hole; did not tag; set 50 sx plug 5170-5095.
6/11/78	Shut down.	6/22/78	Did not tag; spotted 100 sx cmt 5170-4850; tagged @ 5035.
6/12/78	T.I.H. w/tbg; cond. mud.	6/23/78	Spotted 35 sx plug 1650-1525'; spotted 10 sx cmt plug @ surface; cut off 9-5/8" csg spool; erected monument; WELL P&A 6/24/78
6/13/78	Working on pipe.		
6/14/78	Pulling 5 1/2" casing.		
6/15/78	Pulling 5 1/2" casing.		
6/16/78	Pulling 5 1/2" casing.		
6/17/78	Shut down.		
6/18/78	Pulling 5 1/2" casing.		
6/19/78	RD jacks & install BOP.		

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE _____ DATE 6-26-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
FEB 7 1979
[Signature]
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.