

DUPLICATE

# OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

RECEIVED  
AUG 12 1948  
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

|  |        |  |  |
|--|--------|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |        | REPORT ON REPAIRING WELL                       |  |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |        | REPORT ON PULLING OR OTHERWISE ALTERING CASING |  |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                | 9-5/8" | REPORT ON DEEPENING WELL                       |  |
| REPORT ON RESULT OF PLUGGING OF WELL                       |        |  |  |

August 11, 1948

Date

Hobbs, New Mexico

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Gulf Oil Corporation \_\_\_\_\_ Lease \_\_\_\_\_ Well No. 6 in the \_\_\_\_\_  
Company or Operator

SE NE

of Sec. 14

T. 22 S

R. 37 E

N. M. P. M.,  
County.

Drinkard

Field,

Lea

The dates of this work were as follows: Cemented on August 8, 1948. Tested on August 10, 1948.

Notice of intention to do the work was (~~you took~~) submitted on Form C-102 on August 9, 1948 19\_\_\_\_  
and approval of the proposed plan was (~~you took~~) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The hole was washed down and the casing tested with 1200# pressure applied for 30 minutes. The plug was drilled and the casing tested with 1200# pressure applied for 30 minutes. Both tests were OK, and after approval of Mr. Yarbrough, State Oil and Gas Inspector, preparations were made to drill ahead.

Top of cement back of 9-5/8" csg - 1320' per temperature survey.

|  |  |                         |
|--|--|-------------------------|
| Witnessed by <u>G. Stach</u>   | <u>Gulf Oil Corporation</u>                | <u>Drilling Foreman</u> |
| Name   | Company                                    | Title                   |
| Subscribed and sworn before me this _____                                      |  |                         |
| 11th day of August 1948  |  |                         |
| _____<br>Notary Public   |  |                         |
| I hereby swear or affirm that the information given above is true and correct. |  |                         |
| Name <u>E. J. Gallagher</u>  |  |                         |
| Position <u>District Sup't.</u>  |  |                         |
| Representing <u>Gulf Oil Corporation</u>                                       |  |                         |
| Company or Operator  |  |                         |
| My commission expires <u>10-24-49</u>  | Address <u>Box 1667, Hobbs, New Mexico</u> |                         |

Remarks:

APPROVED

Date AUG 12 1948

Ray Yarbrough  
State Oil and Gas Inspector  
Name \_\_\_\_\_  
Title \_\_\_\_\_