

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER-
2. Name of Operator
Gulf Oil Corporation
3. Address of Operator
Box 670, Hobbs, N.M. 88240
4. Location of Well
UNIT LETTER M 660 FEET FROM THE south LINE AND 660 FEET FROM
THE west LINE, SECTION 18 TOWNSHIP 22S RANGE 37E N.M.P.M.

7. Unit Agreement Name
8. Farm or Lease Name
A.L.Christmas (NCT-C)

9. Well No.
6
10. Field and Pool, or Wildcat
Arrowhead

15. Elevation (Show whether DF, RT, GR, etc.)
3443' GL

12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3740' TD.

Set CIBP at 3615' and capped with 35' Class C cement abandoning open hole interval 3665' to 3740'. Found bad casing from 558' to 465'. Loaded hole with abandonment mud. Spotted 100' Class C cement plug from 1300' to 1200' across top of Salt. Set cement retainer at 440' and squeezed from 465' to 558' to surface between 5½" and 9-5/8" annulus with 190 sacks Class C cement. Closed surface valve and squeezed with 120 sacks Class C cement. Spotted 2 sacks cement on top of cement retainer. Spotted 100' cement plug from 100' to surface. Installed dry hole marker and cleaned location. Complete after plugging and abandoning.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED D. F. Berlin TITLE Area Engineer DATE 5-19-77
APPROVED BY John W. Runyan TITLE _____ DATE AUG 20
CONDITIONS OF APPROVAL, IF ANY: