NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans	Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well	Notice of Intention to Plug Back	Notice of Intention to Set Liner	
Notice of Intention o Squeeze	Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)	
Notice of Intention o Gun Perforate	Notice of Intention (Other)	Notice of Intention to (Other) recomplete	X
OIL CONSERVATION COMMIS	SSION Hobbs, New Mexico(Place)	November 3.	1954
Gentlemen:			
Following is a Notice of Inten	tion to do certain work as described below at the	w. B. Kerrel	
immble vil / pefining	Company		
	or Operator) 	MPM., Hlinebry	Pe
me following procedure minment, (2) drill ou 700 feet, (4) test per 5) perforate Blimebry th 2 let shots per fo	FULL DETAILS OF PROPOSED PLAFOLLOW INSTRUCTIONS IN THE RULES As is proposed to recomplete the wat coment plugs and much hole to forations in casing above plug, gas sone from 5430-5460, 5480-55 ot. (7) run tubing with hockmall	AND REGULATIONS) ell: (1) Move in and rig w 5700 feet, (3) set bridge y (5) load hole with salt wat 30, 5530-5555, 5570-5640, 9 packer, (8) displace salt	olug at jer, j660-5685 water wi
ne following procedure quipment, (2) drill ou 700 feet, (4) test per 5) perforate Blinebry ith 2 jet shots per fo 11, (9) treat perforat arough tubing if neces penection by El Paso N	FULL DETAILS OF PROPOSED PLAFOLLOW INSTRUCTIONS IN THE RULES A is proposed to recomplete the wat coment plugs and wash hole to forations in casing above plug.	AND REGULATIONS) sell: (1) Move in and rig w 5700 feet, (3) set bridge g (5) load hole with salt wat 30, 5530-5555, 5570-5640, g packer, (8) displace salt acid, (10) swab in Elinebr over unit and shut in well ine.	olug at ier, 1660-5685 water wi y sene
he following procedure quipment, (2) drill ou 700 feet, (4) test per 6) perforate Elinebry ith 2 jet shots per fo il, (9) treat perforat hrough tubing if neces ownection by El Paso N	FULL DETAILS OF PROPOSED PLAFOLLOW INSTRUCTIONS IN THE RULES As is proposed to recomplete the wat coment plugs and wash hele to forations in casing above plug, gas some from 5430-5460, 5480-55 et, (?) rum tubing with hookmall ed interval with 3000 gallons of sary and test, (11) release work atural Gas Company to the pipe 1	AND REGULATIONS) sell: (1) Move in and rig w 5700 feet, (3) set bridge g (5) load hole with salt wat 30, 5530-5555, 5570-5640, g packer, (8) displace salt acid, (10) swab in Elinebr over unit and shut in well ine.	olug at ier, 1660-5685 water wi y sene
ne following procedure quipment, (2) drill ou 700 feet, (4) test per 6) perforate Blinebry ith 2 jet shots per foll, (9) treat perforat hrough tubing if neces pencetion by El Paso Mais well was previous!	FULL DETAILS OF PROPOSED PLAFOLLOW INSTRUCTIONS IN THE RULES As is proposed to recomplete the wat coment plugs and wash hole to forations in casing above plug, gas some from 5430-5460, 5480-55 et, (7) run tubing with hockmall ed interval with 3000 galloms of sary and test, (11) release work atural Gas Company to the pipe 1: y plugged and abandoned on December 11.	AND REGULATIONS) ell: (1) Move in and rig w 5700 feet, (3) set bridge g (5) load hole with salt wat 30, 5530-5555, 5570-5640, 9 packer, (8) displace salt acid, (10) swab in Blinebs over unit and shut in well ine. ber 7, 1949.	olug at der, 1660-5685 water wi y sens to await
ne following procedure quipment, (2) drill ou 700 feet, (4) test per 5) perforate Blinebry 1th 2 jet shots per foll, (9) treat perforat prough tubing if necessonmection by El Paso Notes well was previously Approved	FULL DETAILS OF PROPOSED PLAFOLLOW INSTRUCTIONS IN THE RULES As is proposed to recomplete the wat coment plugs and much hole to forations in casing above plug, gas some from 5430-5460, 5480-55 et, (7) run tubing with hockmall ed interval with 3000 gallons of sary and test, (11) release work atural Gas Company to the pipe 1 by plugged and abandoned on December 19 plugged and Bandoned on Ban	AND REGULATIONS) sell: (1) Move in and rig w 5700 feet, (3) set bridge; (5) load hole with salt wat 00, 5530-5555, 5570-5640, 9 packer, (8) displace salt acid, (10) swab in Elinebrover unit and shut in well ine. ber 7, 1949.	olug at der, 1660-5685 water wi y sens to await
he following procedure quipment, (2) drill ou 700 feet, (4) test per 6) perforate Blinebry ith 2 jet shots per foil, (9) treat perforathrough tubing if necesonnection by all Paso Mais well was previously his well was previously Approved	FULL DETAILS OF PROPOSED PLAFOLLOW INSTRUCTIONS IN THE RULES As is proposed to recomplete the water common to the plugs and wash hole to forations in casing above plug, gas sone from 5430-5460, 5480-5560, (7) run tubing with hockmall ed interval with 3000 gallons of sary and test, (11) release work atural Gas Company to the pipe 1 by plugged and abandoned on December 19 plugged and December	and regulations) ell: (1) Move in and rig w 5700 feet, (3) set bridge g (5) load hole with salt wat 30, 5530-5555, 5570-5640, 9 packer, (8) displace salt acid, (10) swab in Hinebe over unit and shut in well ine. ber 7, 1949.	olug at ler, 1660-5685 water wi y some to await