

DRILL STEM TEST											
DATE	TESTER	PER	DEPTH	HOLE SIZE	CSG SEAT	SIZE TOP	CHOICE BOTTOM	TOOL OP- FORM. TESTED			RESULTS
								MIN	FROM	TO	
1-18-49	Hall.	5091		6-3/4"	2780	1"	5/8"	90	5091	5155	Rec. 500' salt wr, 160' oil cut mud
2-10-49	"	7265		6-3/4"	2780	1"	5/8"	50	7265	7360	Recovered 90' drilling mud
2-15-49	"	7469		6-3/4"	2780	1"	5/8"	60	7469	7560	Rec. 300' drl mud, 1860' salt water
2-21-49	"	7827		6-3/4"	2780	1"	5/8"	26	7827	7865	Rec 20' drl mud, faint blew
2-22-49	"	7890		6-3/4"	2780	1"	5/8"	95	7890	7935	Rec 20.5 bls. oil
2-27-49	"	7885		4-3/4"	7885	1"	5/8"	101	7885	7900	Rec 900' oil-gas cut mud.
2-28-49	"	7900		4-3/4"	7885	1"	5/8"	120	7900	7920	Rec 4000' oil-gas cut mud
2-1-49	"	7920		4-3/4"	7885	1"	5/8"	75	7920	7940	Rec 320' oil-gas cut mud.

Angular Deviation

Depth	Slope	Instrument
7372	3-1/2°	Totco
7429	3-3/4°	"
7795	3-1/4°	"